



# 04-420HV

## SPECIFICATION SHEET



## EXTRAFLEX®

### ATTRIBUTES:

- 15g Hi Vis Yellow Engineered A4 Liner
- Black Polyurethane Palm Coating

### FEATURES:

- Reinforced Thumb Crotch
- Touchscreen Compatible

### APPLICATIONS:

- Automotive Manufacturing
- Metal Stamping
- Construction
- Sheet Metal Handling
- Steel Processing

### CATEGORY:

- Extraflex®

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

### TECHNOLOGIES:



**⚠** This product can expose you to N,N-Dimethylformamide-which is known to the State of California to cause cancer. For more information go to [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

### SPECIFICATIONS:

- **Liner Materials:** 13g Hi Vis Yellow Engineered A4 Liner
- **Coating Materials:** Black Polyurethane
- **Wrist Design:** Continuous Knit
- **Origin:** PRC
- **Sizes:** XS-XXL

**Armor Guys Reference Number:** 04-420HV

### PACKAGING:

| GLOVE SIZE | XS     | S    | M      | L     | XL    | XXL  |
|------------|--------|------|--------|-------|-------|------|
| CUFF COLOR | Purple | Red  | Yellow | Brown | Black | Blue |
| PER CASE   | 10DZ   | 10DZ | 10DZ   | 10DZ  | 10DZ  | 10DZ |

### PERFORMANCE LEVEL:

**EN388: 4442D** – EN Level 4 Cut Resistance

| ABRASION     | 0 | 1 | 2 | 3 | 4 | 5 |
|--------------|---|---|---|---|---|---|
| CUT          | 0 | 1 | 2 | 3 | 4 | 5 |
| TEAR         | 0 | 1 | 2 | 3 | 4 | 5 |
| PUNCTURE     | 0 | 1 | 2 | 3 | 4 | 5 |
| CUT TDM TEST | A | B | C | D | E | F |

# ARMOR GUYS

• PROTECTED •