



X-SLASH 1124G

X-SLASH, Hi Viz Yellow, 13 Gauge HPPE Engineered Yarn Shell, Black Sandy Nitrile Palm Coating, ANSI Cut A6, Touchscreen, Sanitized®



Key Features & Benefits:

- ANSI A6 Cut Resistance for working with sharp or jagged materials.
- Heavy duty, Engineered HPPE Shell offering level 5 abrasion and level 4 puncture resistance
- Sandy Foam Nitrile palm coating offers maximum abrasion resistance for longer lasting wear in harsh conditions.
- Convenient Touchscreen fingertips.
- Sanitized®

ANSI/ISEA 105



Applications:		Industries:	Certifications/Ratings:	
• Handling Metal Sheets • Handling Sharp/Rough Parts • Cutting Glass Sheets • Structural Components • Press Shop Operators		• Automotive • Chemical • Machinery • Metal Fabrication • General Industry	ANSI ISEA-105 • Cut Level- A6 • Abrasion Level- 5 • Puncture Level- 4	
			ANSI ISEA-138 Impact Level- NR	
Ordering:		Composition	Additional Information	
• Unit of Sale- 1 PR • Case pack- 144 PR • Country of Origin- China • Available Sizes- S-2XL		• 13 Gauge, HPPE Blended Shell • Sandy Foam Nitrile Palm • Knitwrist	Wash using warm water and commercial laundry detergent. Water temperature not to exceed 122°F/ 50°C. Air-dry or tumble-dry with no heat	
			Warning: Cancer & Reproductive Harm- www.P65Warnings.ca.gov	

PACKAGING SPECIFICATIONS

ITEM# 1124G



X-SLASH 1124G

X-SLASH, Hi Viz Yellow, 13 Gauge HPPE Engineered Yarn Shell, Black Sandy Nitrile Palm Coating, ANSI Cut A6, Touchscreen, Sanitized®

Packaging Dimensions

Item Number	Item Number UPC	Dozen UPC	Case UPC	Case L (In)	Case W (In)	Case H (In)	Weight (lbs)
1124GS	196852111107	40196852111105	50196852111102	18.11	11.02	16.93	20.15
1124GM	196852111114	40196852111112	50196852111119	18.11	11.02	16.93	21.10
1124GL	196852111121	40196852111129	50196852111126	18.11	11.02	16.93	23.64
1124GXL	196852111138	40196852111136	50196852111133	18.11	11.02	16.93	26.18
1124G2XL	196852111145	40196852111143	50196852111140	18.11	11.02	16.93	28.09



www.C2VPPE.com

