

X-SLASH 1140G

X-SLASH, Yellow, 10-Gauge Silica/Aramid Shell, Blue Crinkle Finish
Latex Palm Coating, ANSI Cut A5



Key Features & Benefits:

- ANSI A5 Cut Resistance for working with sharp or jagged materials.
- Provides Contact Heat Level 2 Resistance
- Crinkle Finish Latex provides grip in wet and dry conditions
- Seamless Construction offers increased breathability and comfort.
- Elastic Knit Wrist helps prevent dirt & debris from entering the glove.

ANSI/ISEA 105



EN 388



3543

Applications:		Industries:	Certifications/Ratings:
• Waste Handling/Recycling • Material Handling • Glass Handling • Woodworking		• Sanitation • Fishing Industries • Recycling	ANSI ISEA-105 • Cut Level- A5 • Abrasion Level- 4 • Puncture Level- 4
			CE/EN 407:2020, 6.3 & EN ISO 12127-1:2015): • Contact Heat Level 2 (482°F for 15 seconds)
Ordering:		Composition	Additional Information
• Unit of Sale- 1 DZ • Case pack- 6 DZ • Country of Origin- China • Available Sizes- S-XL		• 10 Gauge, 40% Synthetic Yarn, 2% Elastic Shell. • 58% Crinkle Finish Latex Palm • Knitwrist	Wash using warm water and commercial laundry detergent. Water temperature not to exceed 122°F/ 50°C. Air-dry or tumble-dry with no heat
			Warning: Cancer & Reproductive Harm- www.P65Warnings.ca.gov

PACKAGING SPECIFICATIONS ITEM# 1140G



X-SLASH 1140G

X-SLASH, Yellow, 10-Gauge Silica/Aramid Shell, Blue Crinkle Finish
Latex Palm Coating, ANSI Cut A5

Packaging Dimensions

Item Number	Item Number UPC	Inner UPC	Case UPC	Case L (In)	Case W (In)	Case H (In)	Weight (lbs)
1140GS	196852108176		50196852108171	21.26	11.81	11.81	17.86
1140GM	196852108183		50196852108188	21.26	11.81	11.81	17.86
1140GL	196852108190		50196852108195	21.26	11.81	11.81	17.86
1140GXL	196852108206		50196852108201	21.26	11.81	11.81	17.86



www.C2VPPE.com