

EXTRAFLEX® PLUS+

14-300

SPECIFICATION SHEET



CUT



ABR



PUN

EN388

4X42C



ATTRIBUTES:

- 18g, Blue Extraflex® Plus A3 Liner
- Black HCT® MicroFoam Nitrile Palm Coating

FEATURES:

- Reinforced Thumb Crotch
- Touchscreen Compatible
- MicroFoam Coating Ensures Excellent Oil Grip

APPLICATIONS:

- Automotive Manufacturing
- Light Manufacturing
- Sheet Metal Handling
- Metal Stamping
- Construction

CATEGORY:

- Extraflex® Plus

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:



Hybrid Coating Technology

SPECIFICATIONS:

- **Liner Materials:** 18g, Blue Extraflex® Plus A3 Liner
- **Coating Materials:** Black HCT® MicroFoam Nitrile
- **Wrist Design:** Continuous Knit
- **Origin:** PRC
- **Sizes:** XS-XXL

Armor Guys Reference Number: 14-300

PACKAGING:

GLOVE SIZE	XS	S	M	L	XL	XXL
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ

PERFORMANCE LEVEL:

EN388: 4X42C

ABRASION	0	1	2	3	4	5	X
CUT	0	1	2	3	4	5	X
TEAR	0	1	2	3	4	5	X
PUNCTURE	0	1	2	3	4	5	X
CUT TDM TEST	A	B	C	D	E	F	

ARMOR GUYS
• PROTECTED •