

TREE & INDUSTRIAL MARKER



A highly visible marking paint that produces a narrow, concentrated spray for marking trees and lumber at longer distances. Adheres to wet wood and leaves a permanent mark. Color selection is approved by the logging and lumber industry.

Suggested Uses:

Marking trees
 Grading steel
 Identifying lumber
 Mine marking
 Pipe coding
 Grading logs

Packaging:

Cans per case	12
Shipping weight per case	14 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Limited quantity, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 250 linear feet
Cleanup	Paint or lacquer thinner
Flammability	Flammable
Flash point	-4 F
Specific Gravity	0.80
Solids Content	27%
MIR value	0.61, cannot exceed 0.85
HAPs content	0
Storage Temperature	40-100F
Application Temperature	50-90F
Heat Resistance	250° F
Resin System	Alkyd
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch 15 minutes

*At 72F, 50% humidity,
 1.5 mil thickness

**Curing/Recoat time is extended with
 multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60 degree gloss meter

Available Colors:

Part #	Description	UPC Code
16-604	White	043281000734
16-616	Red	043281000758
16-618	Blue	043281000765
16-620	Green	043281000772
16-622	Yellow	043281000789
16-624	Orange	043281000796

12-5-2021