



STRIPE UPRIGHT MARKING PAINT

Fast drying overhead marking paint that is permanent, lead free, and VOC compliant. The can may be sprayed by hand without removing the cap, or you could use it with the Z-606 Marking Wand or the Z-605 Marking Gun.

Suggested Uses:

Mines
 Construction sites
 Mark pipes
 Mark ductwork

Packaging:

Cans per case	12
Shipping weight per case	20 lbs.
Container	20 fluid ounce can
Label weight	17 ounces (469 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 18 square feet
Cleanup	Paint or lacquer thinner
Flammability	Flammable
Flash point	-4F
Specific Gravity	0.83
Solids Content	27%
MIR value	0.62, cannot exceed 0.85
HAPs content	0
Storage Temperature	40-100F
Application Temperature	50-90F
Resin System	V.T. Alkyd
Shelf life	Guaranteed for 2 years
Freeze/Thaw	Up to 7 times without harm

Dry Time*:

To touch	15 minutes
----------	------------

*At 72F, 50% humidity,
 1.5 mil thickness

**Curing/Recoat time is extended with
 multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60 degree gloss meter

Available Colors:

Part #	Description	UPC Code
20-1752	White	043281005418
20-1754	Fluorescent Red	043281005425
20-1757	Fluorescent Orange	043281001250
20-1768	Fluorescent Green	043281005432

12-7-2021