



ULTRA CLEAR LINE SAVER #20-650

Ultra Clear is an exceptionally clear coating that seals and extends the service life of existing paint and chalk marks. Has excellent outdoor performance, dries fast, and sprays in an inverted position. May be applied by hand or with the Z-605 marking gun or Z-606 marking wand.

Suggested Uses:

Warehouse floors
 Construction sites
 Surveying
 Mining

Packaging:

UPC Code	043281008877
Cans per case	12
Shipping weight per case	20 lbs.
Container	20 fluid ounce can
Label weight	15 ounces (433 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 500 linear feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
MIR value	does not exceed 0.85
HAPs content	0
Storage Temperature	40-90F
Application Temperature	50-100F
Shelf life	Guaranteed for 2 years
Tariff Code	3208.10.0000

Dry Time*:

To touch 15 minutes

*At 72F, 50% humidity,
 1.5 mil thickness

**Curing/Recoat time is extended with
 multiple coats and excessively thick coats**

Gloss*: High Gloss, >80

*as measured on a 60 degree gloss meter

12-7-2021