

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/15/2024

Revised On 01/15/2024

1 Identification

Trade name: BLUE FLUORESCENT
Product code: 0000200969
Recommended use: Paint and coatings application.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178 USA
 phone: 815-895-9101
 www.seymourpaint.com
Emergency telephone number: 1-800-255-3924

Seymour of Sycamore
 3041 Dougall Avenue, Suite 503
 Windsor, ONT N9E 1S3 CANADA
 phone: 800-435-4482
 www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.
 Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.
 Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.
 Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labeling:

Hazard statements

Calcium Carbonate
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 May cause respiratory irritation.
 May cause damage to organs through prolonged or repeated exposure.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Use only outdoors or in a well-ventilated area.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a poison center/doctor if you feel unwell.
 Store in a well-ventilated place.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

Physical dangers:

Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

1317-65-3	Calcium Carbonate	25-50%
74-98-6	propane	15-25%
64742-89-8	VM&P Naphtha	10-15%
106-97-8	n-butane	5-10%
64742-47-8	Mineral Spirits	5-10%
142-82-5	heptane	≥5-<10%
110-19-0	Isobutyl Acetate	5-10%

4 First-aid measures

Description of first aid measures

After inhalation:

After skin contact:

After eye contact:

After swallowing:

Supply fresh air; consult doctor in case of complaints.
 Remove contaminated clothing. Wash exposed area with soap and water.
 Rinse opened eye for several minutes under running water. Then consult a doctor.
 Rinse out mouth and then drink plenty of water.
 Rinse mouth with water. Do not induce vomiting.

Information for doctor:

Most important symptoms and effects:

Dizziness

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/15/2024

Revised On 01/15/2024

Trade name: BLUE FLUORESCENT

(Contd. of page 1)

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Extinguishing agents:

Special hazards:

Protective equipment for firefighters:

Additional information

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

Cool endangered receptacles with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Environmental precautions:

Do not allow product to reach sewage systems or ground water.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Fire/explosion protection:

Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

Conditions for safe storage:

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

74-98-6 propane

PEL Long-term value: 1800 mg/m³, 1000 ppm

REL Long-term value: 1800 mg/m³, 1000 ppm

TLV see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL Long-term value: 1900 mg/m³, 800 ppm

TLV Short-term value: 1000 ppm
(EX)

142-82-5 heptane

PEL Long-term value: 2000 mg/m³, 500 ppm

REL Long-term value: 350 mg/m³, 85 ppm
Ceiling limit value: 1800* mg/m³, 440* ppm
*15-min

TLV Short-term value: 500 ppm
Long-term value: 400 ppm

110-19-0 Isobutyl Acetate

PEL Long-term value: 700 mg/m³, 150 ppm

REL Long-term value: 700 mg/m³, 150 ppm

TLV Short-term value: 150 ppm
Long-term value: 50 ppm

Exposure controls

Hygienic protection:

Keep away from foodstuffs and animal feed. Wash hands after use.

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/15/2024

Revised On 01/15/2024

Trade name: BLUE FLUORESCENT

Eye protection: Tightly sealed goggles

(Contd. of page 2)

9 Physical and chemical properties

General Information:

Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C (-47.2 °F)
Flash point:	-19 °C (-2.2 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	40 PSI 2750 hPa
Vapor Pressure:	40 PSI, 2750 hPa
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
Dynamic:	Not determined.
Kinematic:	Not determined.

10 Stability and reactivity

Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Possibility of hazardous reactions:	No dangerous reactions known.
Conditions to avoid	No further relevant information available.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

110-19-0 Isobutyl Acetate

Oral	LD50	4,763 mg/kg (rbt)
------	------	-------------------

Skin effects:	No irritant effect.
Eye effects:	No irritating effect.
Sensitization:	No sensitizing effects known.

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Toxicity Aquatic toxicity: Persistence and degradability: Other information: Bioaccumulative potential: Mobility in soil: Remark: Results of PBT and vPvB assessment PBT: vPvB:	Harmful to aquatic organisms. Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents. No further relevant information available. No further relevant information available. Toxic for fish Not applicable. Not applicable.
--	--

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/15/2024

Revised On 01/15/2024

Trade name: BLUE FLUORESCENT

Other adverse effects: No further relevant information available.

(Contd. of page 3)

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Waste treatment methods

Recommendation: Completely empty cans should be recycled.

Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950
DOT UN1950
 UN1950
UN proper shipping name:
DOT AEROSOLS, flammable
Transport hazard class(es):
Class 2.1 Gases
Marine pollutant: Yes
 Symbol (fish and tree)
Special precautions for user: Warning: Gases
EMS Number: F-D, S-U
DOT
Packaging Group: --

15 Regulatory information

Reglamentación y legislación en materia de seguridad, salud y medio ambiente específicas para la sustancia o la mezcla

Toxic Substances Control Act

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

Hazardous Air Pollutants

1330-20-7 xylene (mix)

100-41-4 ethyl benzene

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

CANADIAN ENVIRONMENTAL

PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

EPA:

142-82-5 heptane

D

110-19-0 Isobutyl Acetate

D

GHS label elements

Precautionary statements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16 Other information

This product was manufactured in the U.S.A.

The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs

Date of preparation / last revision 01/15/2024

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/15/2024

Revised On 01/15/2024

Trade name: BLUE FLUORESCENT

(Contd. of page 4)

VOC: Volatile Organic Compounds (USA, EU)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
EPA: Environmental Protection Agency
IARC: International Agency for the Research of Cancer
NIOSH: National Institute for Occupational Safety and Health
TSCA: Toxic Substances Control Act
CPSC: Consumer Product Safety Commission
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flammable Aerosols 1: Aerosols – Category 1
Gases under Pressure - Liquefied gas: Gases under pressure – Liquefied gas
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2