



# OMNI FLX 2153G

OMNI FLX 2153G, Premium Gray Nylon/Spandex Shell, Black Micro-Foam Palm & 3/4 Back Coated, Nitrile Dotted, Touchscreen Fingertips, Sanitized ®.



## Key Features & Benefits:

- Best in class comfort, lightweight, breathable for all day wear
- Micro-Foam Nitrile 3/4 back coating provides superior grip, durability, dexterity and tactile sensitivity. Nitrile dots for maximum grip.
- Silicone Free
- Convenient Touchscreen Fingertips, Sanitized ®, and Oeko-Tex ® Certified.

| Applications:                                                                                                                                                                     |                                                                                                   | Industries:                                                                                                                                                  | Certifications/Ratings:                                                                                                                                                                                        |    |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| <ul style="list-style-type: none"><li>• Small parts sorting</li><li>• Box Handling</li><li>• Finishing/ Parts Inspection</li><li>• Assembly</li><li>• Material Handling</li></ul> |                                                                                                   | <ul style="list-style-type: none"><li>• Manufacturing</li><li>• Distribution</li><li>• Automotive</li><li>• Construction</li><li>• General Purpose</li></ul> | ANSI ISEA-105                                                                                                                                                                                                  |    |
|                                                                                                                                                                                   |                                                                                                   |                                                                                                                                                              | • Cut Level-                                                                                                                                                                                                   | A1 |
|                                                                                                                                                                                   |                                                                                                   |                                                                                                                                                              | • Abrasion Level-                                                                                                                                                                                              | 6  |
|                                                                                                                                                                                   |                                                                                                   |                                                                                                                                                              | • Puncture Level-                                                                                                                                                                                              | 2  |
|                                                                                                                                                                                   |                                                                                                   |                                                                                                                                                              | ANSI ISEA-138                                                                                                                                                                                                  |    |
|                                                                                                                                                                                   |                                                                                                   |                                                                                                                                                              | Impact Level-                                                                                                                                                                                                  | NR |
| Ordering:                                                                                                                                                                         |                                                                                                   | Composition                                                                                                                                                  | Additional Information                                                                                                                                                                                         |    |
| <ul style="list-style-type: none"><li>• Unit of Sale-</li><li>• Case pack-</li><li>• Country of Origin-</li><li>• Available Sizes-</li></ul>                                      | <ul style="list-style-type: none"><li>1 DZ</li><li>12 DZ</li><li>Vietnam</li><li>SM-2XL</li></ul> | <ul style="list-style-type: none"><li>• 15-Gauge Nylon/Spandex Shell</li><li>• 3/4 Micro-Foam Nitrile Coating</li><li>• Knitwrist</li></ul>                  | Wash using warm water and commercial laundry detergent. Water temperature not to exceed 122°F/ 50°C. Air-dry or tumble-dry with no heat                                                                        |    |
|                                                                                                                                                                                   |                                                                                                   |                                                                                                                                                              | <div>Warning: Cancer &amp; Reproductive Harm<br/><a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a></div> |    |

PACKAGING SPECIFICATIONS

ITEM# 2153G



## OMNI FLX 2153G

OMNI FLX 2153G, Premium Gray Nylon/Spandex Shell, Black Micro-Foam Palm & 3/4 Back Coated, Nitrile Dotted, Touchscreen Fingertips, Sanitized®.

### Packaging Dimensions

| Item Number | Item Number<br>UPC | Inner UPC | Case UPC       | Case<br>L (In) | Case<br>W (In) | Case<br>H (In) | Weight<br>(lbs) |
|-------------|--------------------|-----------|----------------|----------------|----------------|----------------|-----------------|
| 2153GS      | 196852111824       |           | 50196852111829 | 15.75          | 8.66           | 13.39          | 13.23           |
| 2153GM      | 196852111831       |           | 50196852111836 | 16.54          | 9.45           | 13.39          | 15.43           |
| 2153GL      | 196852111848       |           | 50196852111843 | 16.54          | 9.45           | 13.39          | 15.43           |
| 2153GXL     | 196852111855       |           | 50196852111850 | 16.93          | 10.24          | 13.39          | 17.64           |
| 2153G2XL    | 196852111862       |           | 50196852111867 | 16.93          | 10.24          | 13.39          | 17.64           |



[www.C2VPPE.com](http://www.C2VPPE.com)

