



SPECIFICATION SHEET

STYLE: 280-HP241R



Whistler™

Cap Style, HDPE Shell, 4-Point Textile Suspension, Ratchet Adjustment

- Lightweight shell made with UV stabilized High Density Polyethylene (HDPE) reduces worker fatigue
- Shell design includes a rain trough for extra convenience in adverse weather conditions
- 4-Point quick release suspension with strong textile straps and crown comfort pad provides a comfortable and secure fit
- Non-chaffing, replaceable foam sweatband for maximum sweat absorption
- SURE LOCK wheel adjustment system for one hand size adjustments
- Precise height adjustment settings to ensure proper depth

Applications

- Construction Applications
- Road Work
- Excavation
- Industrial Applications

Technical Data

Color	White (-01), Yellow (-02), Orange (-03), Dark Green (-04), Gray (-09), Black (-11), Brown (-12), Dark Gray (-14), Red (-15), Royal (-17), Northern Blue (-18), Pink (-20), Hi-Vis Orange (-31), Hi-Vis Yellow (-44), Lime (-45), Gold (-13), Beige (-10), Hi-Vis Red (-05), Sky Blue (-07), Navy (-08)
Sizes Available	OS
Packaging	Bagged Each
Packed	12/Case
Case Dimensions (cm)	62.23 x 44.45 x 31.75
Case Weight (kg)	6.60
Country of Origin	Canada
Shell Material	HDPE
Shell	Non-Vented
Brim Style	Cap Style
Brim Length	Standard
Size Adjustment	Wheel Ratchet
Suspension	4 Point Nylon Webbing Cradle
Chin Strap	--
Sweatband	Felt Lined Foam
Construction	--
Certifications	CSA Z94.3 Certified, ANSI/ISEA Z89.1, EN 397, TAA Compliant

Performance Data

ANSI Type	Type I
Electrical Class	E

Care Instructions

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2022-03-01