



SPECIFICATION SHEET

280-HP641R

DYNAMIC KILIMANJARO FULL BRIM NON-VENTED HARD HAT WITH WHEEL RATCHET

- Meets -ANSI/ISEA Z89.1 Type 1 and CSA Z94.1 Type 1 requirements
- Fulfills Class E Electrical Insulation requirements
- Lightweight shell made with UV stabilized High Density Polyethylene (HDPE) reduces worker fatigue
- 4-Point quick release suspension with strong textile straps and crown comfort pad provides a comfortable and secure fit
- SURE LOCK wheel adjustment system for one hand size adjustments
- Precise height adjustment settings to ensure proper depth
- Low nape strap provides a secure fit, allowing the hard hat to stay on your head even when workers are looking down or bending over
- Non-chaffing, replaceable foam sweatband for maximum sweat absorption
- Universal accessory slots accommodate a variety of eye, face and hearing protection products
- Custom logo imprinting available on all four sides of the hard hat

APPLICATIONS

- Construction
- Oil & gas
- Mining
- Demolition
- High pressure jetting
- Energy companies
- Certain emergency services (FEMA & USAR)
- High-risk environments where high impact situations are of concern

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

TECHNICAL DATA

MATERIAL	Shell: High Density Polyethylene, Recyclable Suspension: 4 point quick release clips, nylon strap and crown protection pad Sweatband: Foam PE		
COLOR	☐ White (-01) ☐ Orange (-03) ☐ Blue (-08) ☐ Red (-15) ☐ Yellow (-02) ☐ Green (-04) ☐ Gray (-14) ☐ Light Gray (-09)		
HAT SIZE	6 - 8 (19" - 25")		
EACH WEIGHT	2.1 lbs / 0.95 kg		
PACKAGING	12 per case		
CASE	23" x 20" x 26" / 58.42cm x 50.80cm x 66.04cm		
CASE WEIGHT	16 lbs / 7.25 kg		
COO	Canada		



BARCODES

ITEM	EACH	CASE
☐ 280-HP641R-01	620606001395	10620606001392
☐ 280-HP641R-02	620606001401	10620606001408
☐ 280-HP641R-03	620606001418	10620606001415
☐ 280-HP641R-04	620606001425	10620606001422
☐ 280-HP641R-08	620606001463	10620606001461
☐ 280-HP641R-09	620606001470	10620606001477
☐ 280-HP641R-14	620606007045	10620606007042
☐ 280-HP641R-15	620606001517	10620606001514

DIMENSIONS (in)

