



SPECIFICATION SHEET

280-EVLV

INDUSTRIAL HEIGHT SAFETY HELMET WITH LIGHTWEIGHT ABS SHELL, INTEGRATED ANSI Z87.1 EYE PROTECTION, 6-POINT POLYESTER SUSPENSION AND WHEEL RATCHET ADJUSTMENT

- Fully retractable integrated eye protector. ANSI Z87+ Impact Resistant
- Pivot arms allow VISTALens to be retracted and deployed seamlessly
- Pivots smoothly giving a wide arc allowing for prescription spectacles to be worn
- TPR seal on the lens molds to moulds to the wearer's face, creating a good seal for better projectile protection and increased comfort
- 6-Point polyester textile suspension system offers unrivaled comfort without compromising performance
- Revolution™ Wheel Ratchet is easy to use and creates a firm comfortable fit
- Meets ANSI/ISEA Z89.1, Type I, Class C requirements
- Universal accessory slots accepts virtually any competitors' accessories
- Chamlon™ sweatband

APPLICATIONS

Protection from falling debris and low hanging objects in industrial and construction applications.

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

TECHNICAL DATA

MATERIAL	Shell: ABS Suspension: HDPE strap & clips, polyester straps Sweatband: Cotton core with PU coating
COLOR	01W - ☐ White ☐ White Front 01S - ☐ White ☐ Smoke Front 50B - ☒ Blue ☒ Blue Front 50S - ☒ Blue ☐ Smoke Front
SIZES	Adjustable
WEIGHT	0.92 lbs / 415 g
PACKAGING	Individually bagged, 10 per case
CASE	9.5" x 23" x 18" / 24.1 cm x 58.4 cm x 45.7 cm
CASE WEIGHT	8.4 lbs / 3.8 kg
COO	UK

BARCODES

ITEM	EACH	CASE
☐ 280-EVLV-01W	5038428315135	5038428405478
☐ 280-EVLV-01S	5038428361736	5038428405539
☒ 280-EVLV-50B	5038428361743	5038428405560
☒ 280-EVLV-50S	5038428361750	5038428405614



DIMENSIONS (in/cm)

	OSFA
A	11.02 / 28
B	5.9 / 15

