



SPECIFICATION SHEET

280-HP641RV

DYNAMIC KILIMANJARO FULL BRIM VENTED HARD HAT WITH WHEEL RATCHET

- Meets -ANSI/ISEA Z89.1 Type 1 requirements
- Fulfills Class C electrical rating
- Vented for maximum air flow
- Lightweight shell made with UV stabilized High Density Polyethylene (HDPE) reduces worker fatigue
- 4-Point quick release suspension with strong textile straps and crown comfort pad provides a comfortable and secure fit
- SURE LOCK wheel adjustment system for one hand size adjustments
- Precise height adjustment settings to ensure proper depth
- Low nape strap provides a secure fit, allowing the hard hat to stay on your head even when workers are looking down or bending over
- Non-chaffing, replaceable foam sweatband for maximum sweat absorption
- Universal accessory slots accommodate a variety of eye, face and hearing protection products
- Custom logo imprinting available on all four sides of the hard hat

APPLICATIONS

- Construction
- Oil & gas
- Mining
- Demolition
- High pressure jetting
- Energy companies
- Certain emergency services (FEMA & USAR)
- High-risk environments where high impact situations are of concern

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

TECHNICAL DATA

MATERIAL	Shell: High Density Polyethylene, Recyclable Suspension: 4 point quick release clips, nylon strap and crown protection pad Sweatband: Foam PE		
COLOR	☐ White (-01) ☐ Orange (-03) ☐ Blue (-08) ☐ Red (-15) ☐ Yellow (-02) ☐ Green (-04) ☐ Gray (-14) ☐ Light Gray (-09)		
HAT SIZE	6 - 8 (19" - 25")		
EACH WEIGHT	2.1 lbs / 0.95 kg		
PACKAGING	12 per case		
CASE	23" x 20" x 26" / 58.42cm x 50.80cm x 66.04cm		
CASE WEIGHT	16 lbs / 7.25 kg		
COO	Canada		



BARCODES

ITEM	EACH	CASE
☐ 280-HP641RV-01	620606006796	10620606006793
☐ 280-HP641RV-02	620606006802	10620606006809
☐ 280-HP641RV-03	620606006819	10620606006816
☐ 280-HP641RV-04	620606006826	10620606006823
☐ 280-HP641RV-08	620606006864	10620606006861
☐ 280-HP641RV-09	620606006871	10620606006878
☐ 280-HP641RV-14	620606007052	10620606007059
☐ 280-HP641RV-15	620606006925	10620606006922

DIMENSIONS (in)

