



SPECIFICATION SHEET

63-532PF

AMBI-DEX® AXLE DISPOSABLE NITRILE GLOVE, POWDER FREE WITH TEXTURED GRIP - 4 MIL BLUE

- Economical puncture resistance with great comfort, dexterity and tactile sensitivity
- Textured grip provides a good grip in wet or dry environments
- Ambidexterous
- Powder-Free for clean comfort and superior tactile sensitivity
- Contains no natural rubber latex proteins
- Beaded cuff
- Complies with FDA food handling requirements, 21 CFR 177.2600
- CFIA approved
- AQL 4.0

APPLICATIONS

- Painting & Print
- Tattoo Shops
- Automotive

TECHNICAL DATA

MATERIAL	Nitrile				
COLOR	Blue				
CUFF STYLE	Rolled beaded				
SIZES	S - XXL				
PACKAGING	100 gloves per dispenser box; 10 boxes per case (1,000 gloves)				
CASE	14.1" x 10.2" x 9.6" / 36cm x 26cm x 24.5cm				
CASE WEIGHT	S	M	L	XL	XXL
	12.3 lbs 5.6 kg	13.2 lbs 6.0 kg	14.3 lbs 6.5 kg	15.4 lbs 7.0 kg	17 lbs 7.7 kg
COO	Malaysia				

ELONGATION INFORMATION

BEFORE AGING		AFTER ACCELERATED AGING	
Tensile Strength (minimum)	Elongation (minimum)	Tensile Strength (minimum)	Elongation (minimum)
(Mpa)	%	(Mpa)	%
14	500	14	400

BARCODES


ITEM	BAG	DISPENSER	CASE
63-532PF/S	---	616314032240	02616314032240
63-532PF/M	---	616314032257	02616314032257
63-532PF/L	---	616314032264	02616314032264
63-532PF/XL	---	616314032271	02616314032271
63-532PF/XXL	---	616314227776	02616314227774



DIMENSIONS (in/cm)

	S	M	L	XL	XXL
A	9.4 / 24.0	9.4 / 24.0	9.4 / 24.0	9.4 / 24.0	9.4 / 24.0
B	3.3 / 8.4	3.7 / 9.4	4.1 / 10.5	4.4 / 11.3	4.8 / 12.3

Palm Thickness: 0.10mm (± 0.02mm)
Finger Tip Thickness: 0.12mm (± 0.02mm)



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.