

PILOT

HIGH REQUIREMENTS AT THE SERVICE OF SAFETY

Its co-injected, ventilated frame guarantees unequalled adaptability and comfort.



PILOT ADVANTAGES

- ▶  PLATINUM® COATING
- ▶ EXCELLENT FIELD OF VISION
- ▶ PC/TPR TWIN-MATERIAL FRAME
- ▶ ADJUSTABLE STRAP
- ▶ FITS OVER PRESCRIPTION GLASSES

 PLATINUM®

bolle.
SAFETY

PILOT

FOR CLEAN ENVIRONMENTS AND EXTREME CONDITIONS

Its co-injected, ventilated frame guarantees unequalled adaptability and comfort.



3.1 OZ

SPECIFICATIONS

VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS	INDIVIDUAL	INNER PACK	MASTER PACK
Clear	40274	Z87+U6	Z87+/Z94	Anti-scratch/Anti-fog (+P)	0-54917-32686-9	10	120
Twilight	40275	Z87+U6	Z87+/Z94	Anti-scratch/Anti-fog (+P)	0-54917-32689-0	10	120

CHARACTERISTICS



Lens Material: Polycarbonate
Lens Thickness: 2.1 mm
Frame Material: PC+TPR
Base Curve: 5.5
Strap: Nylon

PLATINUM®

This permanent coating on both sides of the lens gives them a high resistance to scratching, to the most aggressive chemicals and delays the onset of fogging. In all circumstances and at all times the PLATINUM® lens innovation guarantees your eyes improved protection.



CLEANING Lenses should be cleaned regularly. Bolle Safety recommends using the B-clean lens cleaning system.

STORAGE Must be stored in a clean, dry environment. After each use, keep product in a microfiber pouch or rigid case.

REPLACEMENT If lenses or frames are pitted, scratched or damaged, the complete product must be replaced.