

ANCHOR

ROOF ANCHOR

Single Use - Raised - Zinc Coated Steel

DXFP841001

BENEFITS AND FEATURES

The DEWALT Single Use, Raised Roof Anchor is designed for use on the ridge of pitched roofs. The anchor is made of coated steel with a 1 in. (2.54 cm) D-Ring style connection point.

DURABILITY: The one-piece design and zinc plated galvanized steel provides a long lasting temporary anchor point.

COMPACT AND LIGHTWEIGHT: At only 1.3 lbs (0.59kg.) this anchor allows for easy installation.

STRENGTH: Meets OSHA and ANSI standards of 5,000 lbs. (23kN) anchor point.

ECONOMICAL: Provides an economical means to ensure sufficient anchor points are in place throughout the construction process.



SPECIFICATIONS

Overall Height: 6.38 in. [16.2 cm.] **Width:** 2.23 in. [5.68 cm.]

Capacity: 310 lbs.(140 Kg.)

Breaking Strength: 5,000 lbs. (2267) kg.

Materials of construction: Steel

RELEVANT STANDARDS

Meets ANSI Z359.18-2017, OSHA 1926.502, 1910.140

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY