



POLYURETHANE DIPPED



POLYURETHANE



13 GAUGE



ABRASION



PUNCTURE



TEAR



CUT



IMPACT



HIGH VISIBILITY

GL402CB

HPPE | Polyurethane | TPR

ANSI/ISEA 105



ANSI / ISEA 138



EN388



4X43DP

ANSI/ISEA 105-2015 – CUT A4 | ABRASION 3 | PUNCTURE 4

ANSI/ISEA 138-2019 – IMPACT 1

EN388 – ABRASION 4 | CUT X | TEAR 4 | PUNCTURE 3 | CUT TDM-100 D | IMPACT P

Polyurethane coating on the palm and fingers for good grip and precision handling // 13 gauge HPPE cut-resistant liner delivers cool comfort for all-day wear // Custom-designed high-visibility impact protection shields the back of hand and allows for maximum visibility // Glove design offers excellent touch sensitivity and low particulate shed // Knit cuff creates a snug fit to keep out debris

Suggested Applications

Automotive // General Duty/Purpose // Glass Cutting // Parts Assembly // Sheet Metal Handling // Mechanical // Mining // Oil & Gas

Glove Breakdown

Type: Dipped Glove
Material: Polyurethane
Outer Liner: 13 Gauge HPPE
Cuff: HPPE + Latex Elastic
Impact: Thermoplastic Rubber

⚠ WARNING: Cancer and Reproductive Harm – P65Warnings.ca.gov
This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.



Packaging

	Inner Polybag	Outer Polybag	Case
GL402CB	1 Pair	12 Pair	60 Pair
Made in China			

Product markings may vary // Updated as of 01.24

Glove Sizing

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.