

GL404C

HPPE | Polyurethane

ANSI/ISEA 105-2016 – CUT A4 | PUNCTURE 4 | ABRASION 4
EN388: 2016 – 4X42D

Polyurethane palm coating // 13 gauge HPPE liner //
Hi-vis // Touch sensitivity // Low particulate shed

GL404C S – 2XL

Suggested Applications

Metal Fabrication // Manufacturing //
Automotive // Construction

Glove Breakdown

Type: Dipped Glove
Material: Polyurethane
Liner: 13 Gauge HPPE
Cuff: HPPE + Latex Elastic

This product contains components that may be a potential risk to allergic reactions [latex in the wrist cuff]. Do not use in the event of hypersensitivity signs or a known allergy to latex.

Testing Performance

EN388: 2016 – 4X42D

Abrasion	1	2	3	4		
Circular Blade Cut	1	2	3	4	5	X
Tear	1	2	3	4		
Puncture	1	2	3	4		
Cut TDM-100	A	B	C	D	E	F
Impact Rated	P	F	X			

ANSI/ISEA 105-2016

Cut	1	2	3	4	5	6	7	8	9
Abrasion	1	2	3	4	5	6			
Puncture	1	2	3	4	5				



PU



Abrasion



Cut



Tear



Puncture



High-visibility



Product markings may vary. Refer to the product sheet for the most current test report results.

Glove Sizing

The color of the binding around the cuff indicates the glove size.

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Packaging

Pack: 12 pair
Case: 120 pair
Country of Origin: China