



Nitrile Dipped Glove

Product Sheet

GL613C

HPPE | Nitrile | Micro-Foam

ANSI/ISEA 105-2016 – CUT A4 | ABRASION 5 | PUNCTURE 3
EN388: 2016 – 4X42D

Nitrile micro-foam palm coating // 18 gauge HPPE liner
// Good grip in all conditions // Reinforced thumb saddle
// Touchscreen capability

GL613C S – 2XL

Suggested Applications

Assembly Line // Construction // HVAC // Handling Oily
Parts // Furniture // Manufacturing

Glove Breakdown

Type: Dipped Glove
Material: Nitrile Micro-Foam
Liner: 18 Gauge HPPE
Cuff: HPPE + Latex Elastic

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Testing Performance

EN388: 2016 – 4X42D

Abrasion	1	2	3	4		
Circular Blade Cut	1	2	3	4	5	X
Tear	1	2	3	4		
Puncture	1	2	3	4		
Cut TDM-100	A	B	C	D	E	F
Impact Rated	P	F	X			

ANSI/ISEA 105-2016

Cut	1	2	3	4	5	6	7	8	9
Abrasion	1	2	3	4	5	6			
Puncture	1	2	3	4	5				



Nitrile



Abrasion



Cut



Tear



Puncture



Touchscreen



Glove Sizing

The color of the binding around the cuff indicates the glove size.

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Packaging

Pack: 12 pair
Case: 120 pair
Country of Origin: China