



# BULLHEAD SAFETY® HEARING PROTECTION

## PVC-Free Polyurethane Foam Earplug Dispenser, 500 Pairs

### DESCRIPTION

Counter top earplug dispensers offer quick and easy access to earplugs. Just turn the 360 degree funnel and earplugs will dispenser below. This allows workers to conveniently retrieve their earplugs in hygienic fashion. It contains single-use foam earplugs for effective protection against hearing damage by greatly reducing environmental noise.

This dispenser comes pre-filled (HP-FDL1).

Refill bag also available (HP-FDL1-RF).



### INDUSTRY

|               |                  |
|---------------|------------------|
| Airport Crews | Utility Work     |
| Construction  | Transportation   |
| Automotive    | Manufacturing    |
| Printing      | Waste Management |

### FEATURES

- 500 pairs per dispenser or refill bag
- Two mounting holes on the dispenser stand
- 100% PVC-free PU single-use earplugs
- Expandable, slow rebound bullet shaped foam
- Made of soft non-allergenic material
- Noise Reduction Rating (NRR) 32 dB

### SPECIFICATIONS

| STYLE                         | COLOR           | DISPENSER DIMENSIONS | PAIRS/DISPENSER | RETAIL READY | ANSI S3. 19-1974 NRR RATING |
|-------------------------------|-----------------|----------------------|-----------------|--------------|-----------------------------|
| Counter Top Earplug Dispenser | Black and Clear | 6.5 x 7 x 18.25      | 500             | Yes          | 32 dB                       |

#### ANSI S3.19-1974 SOUND ATTENUATION DATA:

| FREQUENCY (HZ)          | 125  | 250 | 500  | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 | NRR   |
|-------------------------|------|-----|------|------|------|------|------|------|------|-------|
| MEAN ATTENUATION (DB)   | 35.2 | 37  | 43.9 | 41.8 | 39.4 | 44.8 | 45.4 | 48.4 | 46.2 | 32 DB |
| STANDARD DEVIATION (DB) | 5.7  | 4.3 | 3.8  | 4.7  | 3.0  | 4.4  | 4.3  | 3.2  | 4.1  |       |

#### EN 352-2: 2002 SOUND ATTENUATION DATA:

| FREQUENCY (HZ)          | 63          | 125       | 250       | 500       | 1000 | 2000 | 4000 | 8000 |
|-------------------------|-------------|-----------|-----------|-----------|------|------|------|------|
| SOUND ATTENUATION (DB)  | 24.1        | 29.4      | 33.9      | 33.6      | 35.5 | 35.8 | 45.1 | 45.7 |
| STANDARD DEVIATION (DB) | 4.6         | 5.2       | 5.9       | 6.4       | 5.9  | 3.9  | 3.6  | 5.7  |
| ASSUMED PROTECTION (DB) | 19.5        | 24.2      | 28        | 30.2      | 29.6 | 31.9 | 41.5 | 40   |
|                         | SNR = 34 DB | H = 34 DB | M = 31 DB | L = 29 DB |      |      |      |      |

ITEM **HP-FDL1** NRR **32 DB**



### PACKAGING

|                         | QUANTITY       | HP-FDL1        |
|-------------------------|----------------|----------------|
| INNER BOX               | 500 PAIRS/DISP | 816368025803   |
| CASE                    | 4 DISP/CASE    | 10816368025800 |
| CASE WEIGHT (IN POUNDS) |                | 15             |

13915 Radium St NW  
Ramsey, MN 55303

763-450-0110  
sales@BullheadSafety.com

BullheadSafety.com

