



BULLHEAD SAFETY® HEARING PROTECTION

Premium High-Visibility Foldable Earmuffs

DESCRIPTION

The HP-M2 is a foldable earmuff with high level attenuation. Conveniently folds away for easy storage. Over-the-head banded design provides maximum versatility for use with other PPE. Features ABS cups for their durability and impact resistance. The soft PVC cushions allows comfort in extended wearing conditions. NRR 23 dB.

Each item is individually packaged in a box for retail sale.

INDUSTRY

Assembly	Welding
Cleaning	Construction
Demolition	Machine Operation
Electrical	Painting
Facility Maintenance	Transportation
Grinding	Manufacturing
Sanding	



ITEM **HP-M2** NRR **23 DB**

FEATURES

- Adjustable and flexible reinforced plastic headband with four-point suspension offers a custom fit
- Lightweight earmuff for extended wearability
- ABS (Acrylonitrile Butadiene Styrene) cups provide impact resistance
- Soft PVC ear cushions deliver long-wearing comfort
- Stainless steel wires prevent rust and corrosion



SPECIFICATIONS

CUPS	COLOR	CUSHION MATERIAL	HEADBAND	SUSPENSION WIRES	RETAIL READY	ANSI S3.19-1974 NRR RATING
ABS, Impact Resistance	Black and Yellow/ Green	Soft PVC	Adjustable, Flexible, Reinforced and has a 4-Point Suspension	Stainless Steel	Yes	23 dB

ANSI S3.19-1974 SOUND ATTENUATION DATA:

FREQUENCY (HZ)	125	250	500	1000	2000	3150	4000	6300	8000	NRR
MEAN ATTENUATION (DB)	16.2	17.8	28.7	33	34.1	38.6	38.5	38.7	37.9	23 dB
STANDARD DEVIATION (DB)	3.8	1.8	2.5	2.9	2.8	2.3	2.8	3.5	4.1	

EN 352-2: 2002 SOUND ATTENUATION DATA:

FREQUENCY (HZ)	63	125	250	500	1000	2000	4000	8000
SOUND ATTENUATION (DB)	18.8	15.4	17.9	27.8	36.3	35.4	42.4	39.5
STANDARD DEVIATION (DB)	4.1	4.1	3.5	2.7	3.7	3.6	2.6	5.4
ASSUMED PROTECTION (DB)	14.7	11.3	14.4	25.1	32.6	31.8	39.8	34.1
	SNR = 28 dB		H = 34 dB		M = 26 dB		L = 17 dB	

PACKAGING

	QUANTITY	HP-M2
EACH PAIR	1	810292029647
CASE	20 PK/CASE	10810292029644
CASE WEIGHT (IN POUNDS)		14.65

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
sales@BullheadSafety.com

BullheadSafety.com

