



Ridgeline® Cap Style

ANSI • CSA • (with clip only)

Shell constructed from ABS material // Low profile design // Available with 4- point and 6-point ratchet suspensions // Swinging hinge points // 4-position harness // Adjusts from 6½ to 8 // Rear padded suspension // Replacement suspensions available // Vented pressure pad // Universal accessory slots // Passes Reverse Orientation, High-Temperature (HT) and Low Temperature (LT) // Vented cap style hard hats are rated Class C and do not meet Class E or G safety standards // Custom imprinting available

Vented Cap Style

4-Point Ratchet | 7 Variations

HP44110V •	White
HP44112V •	Gray
HP44120V •	Red
HP44130V •	Yellow
HP44131V •	Hi-Vis Lime
HP44141V •	Hi-Vis Orange
HP44160V •	Blue



Standard Cap Style

4-Point Ratchet | 15 Variations

HP44110 •	White
HP44110C ••	White
HP44112 •	Gray
HP44113 •	Slate Gray
HP44120 •	Red
HP44130 •	Yellow
HP44130C ••	Yellow
HP44131 •	Hi-Vis Lime
HP44131C ••	Hi-Vis Lime
HP44135 •	Green
HP44141 •	Hi-Vis Orange
HP44160 •	Blue
HP44162 •	Light Blue
HP44165C ••	Dark Blue
HP44170 •	Hi-vis Pink

6-Point Ratchet | 7 Variations

HP46110 •	White
HP46120 •	Red
HP46130 •	Yellow
HP46131 •	Hi-Vis Lime
HP46135 •	Green
HP46141 •	Hi-Vis Orange
HP46160 •	Blue



Non-vented head protection meets ANSI Z89.1 (•), Type 1, Class E, G and C. Vented head protection meets ANSI Z89.1 (•), Type 1, and Class C. Hi-vis colors have been tested for the "HV" mark. Some options meet Canadian CSA Z94.1 - 2015 (•), Type 1, Class E, G and C standards – SEI third-party certification. For specific options visit our website or contact your sales representative.



Hydro Dipped

4-Point Ratchet Hydro Dipped | 10 Variations

	HP44116 •	Matte White Graphite Pattern
	HP44116S •	Shiny White Graphite Pattern
	HP44117 •	Matte Black Graphite Pattern
	HP44117C •	Matte Black Graphite Pattern (CSA with clip only)
	HP44117S •	Shiny Black Graphite Pattern
	HP44118 •	Matte Copper Pattern
	HP44119 •	Matte Camo Pattern
	HP44121 •	Matte Red Pattern
	HP44122 •	Matte Blue Pattern
	HP44MIX •	HP44116 [4], HP44117 [4], HP44118 [4], and HP44119 [4]



Vented Hydro Dipped

4-Point Ratchet Hydro Dipped | 2 Variations

	HP44116SV •	Shiny White Graphite Pattern
	HP44117V •	Matte Black Graphite Pattern



HPRBANDR – Ridgeline Cap Style and Full Brim Hard Hat Sweat Band



HPR441 – 4-point Ratchet Replacement Suspension



HPR461 – 6-point Ratchet Replacement Suspension

Materials

Shell: high impact acrylonitrile-butadiene-styrene (ABS)

Suspension: high density polyethylene (HDPE) & high impact nylon

Sweat band: polyester fabric & polyurethane (PU) foam

General Specifications

Weight: 358 gm

Shell thickness: 2 - 4 mm

Dimensions: 28 cm x 22 cm x 15.2 cm

Suspension adjust sizing: 6.5 - 8

Suspensions: 4-point & 6-point ratchet

Styles: vented & non-vented

Standards: ANSI/ISEA Z89.1-2014 and Cert. Mod. - CAN/CSA Z94.1-15

Types: Type 1

Classes: non-vented Class E, G, and C | vented Class C

Optional features: reverse donning, hi-vis colors (HV), lower temperature (LT), higher temperature (HT)

Markings

Types: Type 1 offers protection to the top of the head

Classes: Class E (electrical) rated for 20,000 volts | Class G (general) rated for 2,200 volts | Class C (conductive) does not offer electrical protection

Tested and marked for reverse orientation

HV: meets all requirements for high visibility

LT: provides protection at low temperatures -22°F

HT: provides protection at high temperatures 140°F

Date code: indicates month and year when the shell was molded – does not indicate service life



Product Guidelines

Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use

Never alter or modify the shell or suspension system

Inspect the hard hat each time before use and replace if there is ANY sign of damage

Replace hard hat after it receives a considerable impact

Accessories such as liners have not been tested to the requirement of this standard

Clean only with mild soap and lukewarm water

Store hard hat in a clean, dry place that is out of direct sunlight

Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat

Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage