



Ridgeline® Cap Style

ANSI/ISEA • CAN/CSA • (with clip only)

Shell constructed from ABS material // Low profile design // Available with 4-point and 6-point ratchet suspensions // Swinging hinge points // 4-position harness // Adjusts from 6.5 - 8 // Rear padded suspension // Replacement suspensions available // Vented pressure pad // Universal accessory slots // Passes Reverse Orientation, High-Temperature (HT) and Low Temperature (LT) // Vented cap style hard hats are rated Class C and do not meet Class E or G safety standards // Custom imprinting available



Vented Cap Style

4-Point Ratchet | 7 Variations

- HP44110V • White
- HP44112V • Gray
- HP44120V • Red
- HP44130V • Yellow
- HP44131V • Hi-vis Lime
- HP44141V • Hi-vis Orange
- HP44160V • Blue



Standard Cap Style

4-Point Ratchet | 15 Variations

- HP44110 • White
- HP44110C • White
- HP44112 • Gray
- HP44113 • Slate Gray
- HP44120 • Red
- HP44130 • Yellow
- HP44130C • Yellow
- HP44131 • Hi-vis Lime
- HP44131C • Hi-vis Lime
- HP44135 • Green
- HP44141 • Hi-vis Orange
- HP44160 • Blue
- HP44162 • Light Blue
- HP44165C • Dark Blue
- HP44170 • Hi-vis Pink

6-Point Ratchet | 7 Variations

- HP46110 • White
- HP46120 • Red
- HP46130 • Yellow
- HP46131 • Hi-vis Lime
- HP46135 • Green
- HP46141 • Hi-vis Orange
- HP46160 • Blue



Non-vented head protection meets ANSI/ISEA Z89.1-2014 (•), Type 1, Class E, G and C. Vented head protection meets ANSI/ISEA Z89.1-2014 (•), Type 1, and Class C. Hi-vis colors have been tested for the "HV" mark. Some options meet Canadian CSA Z94.1 - 2015 (•), Type 1, Class E, G and C standards – SEI third-party certification. For specific options visit our website or contact your sales representative.

REALTREE AP © 2013 of Jordan Outdoor Enterprises, Ltd., all rights reserved.



Hydro Dipped

4-Point Ratchet | 12 Variations

- HP44116 • Matte White Graphite Pattern
- HP44116C • Matte White Graphite Pattern (CSA with clip only)
- HP44116S • Shiny White Graphite Pattern
- HP44117 • Matte Black Graphite Pattern
- HP44117C • Matte Black Graphite Pattern (CSA with clip only)
- HP44117S • Shiny Black Graphite Pattern
- HP44118 • Matte Copper Graphite Pattern
- HP44119 • Realtree AP® (Matte)
- HP44121 • Matte Red Graphite Pattern
- HP44122 • Matte Blue Graphite Pattern
- HP44123 • Matte Silver Graphite Pattern
- HP44124 • Matte Lime Graphite Pattern



Vented Hydro Dipped

4-Point Ratchet | 2 Variations

- HP44116SV • Shiny White Graphite Pattern
- HP44117V • Matte Black Graphite Pattern



HPRBANDR – Ridgeline Cap Style
and Full Brim Hard Hat Sweat Band



HPR441 – 4-point Ratchet
Replacement Suspension



HPR461 – 6-point Ratchet
Replacement Suspension

Materials

Shell: high impact acrylonitrile-butadiene-styrene (ABS)
Suspension: high density polyethylene (HDPE) & high impact nylon
Sweat band: polyester fabric & polyurethane (PU) foam

General Specifications

Weight: 358 gm
Shell thickness: 2 - 4 mm
Dimensions: 28 cm x 22 cm x 15.2 cm
Suspension adjust sizing: 6.5 - 8
Suspensions: 4-point & 6-point ratchet
Styles: vented & non-vented
Standards: ANSI/ISEA Z89.1-2014 and Cert. Mod. - CAN/CSA Z94.1-15
Types: Type 1
Classes: non-vented Class E, G, and C | vented Class C
Optional features: reverse donning, hi-vis colors (HV), lower temperature (LT), higher temperature (HT)

Markings

Types: Type 1 offers protection to the top of the head
Classes: Class E (electrical) rated for 20,000 volts | Class G (general) rated for 2,200 volts | Class C (conductive) does not offer electrical protection
Tested and marked for reverse orientation 
HV: meets all requirements for high visibility
LT: provides protection at low temperatures -22°F
HT: provides protection at high temperatures 140°F
Date code: indicates month and year when the shell was molded –   does not indicate service life

Product Guidelines

Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use
Never alter or modify the shell or suspension system
Inspect the hard hat each time before use and replace if there is ANY sign of damage
Replace hard hat after it receives a considerable impact
Accessories such as liners have not been tested to the requirement of this standard
Clean only with mild soap and lukewarm water
Store hard hat in a clean, dry place that is out of direct sunlight
Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat
Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage

REALTREE AP © 2013 of Jordan Outdoor Enterprises, Ltd., all rights reserved.