



Ridgeline® Full Brim ANSI • CSA •

Shell constructed from ABS material // Ratchet suspension is easy to adjust, allowing you to modify the fit while wearing the hat // Available in 4-point and 6-point ratchet suspension // 4-point ratchet suspension may be converted to 6-point ratchet suspension with optional strap (HP6PTSUS) // Replaceable ratchet suspensions available // Replaceable sweat band— padded fabric and polyurethane foam // Passes high temperature (HT) and low temperature (LT) // Custom imprinting available

Vented Full Brim

4-Point Ratchet Vented | 7 Variations

HP54110V ••	White
HP54113V ••	Slate Gray
HP54130V ••	Yellow
HP54131V ••	Hi-Vis Lime
HP54141V ••	Hi-Vis Orange
HP54160V ••	Blue
HP54117V ••	Matte Black Graphite

Hydro Dipped

4-Point Ratchet Hydro Dipped | 10 Variations

HP54116 ••	Matte White Graphite Pattern
HP54116S ••	Shiny White Graphite Pattern
HP54117 ••	Matte Black Graphite Pattern
HP54117S ••	Shiny Black Graphite Pattern
HP54117V ••	Matte Black Graphite Pattern (Vented)
HP54118 ••	Matte Copper Pattern
HP54119 ••	Matte Camo Pattern
HP54121 ••	Matte Red Pattern
HP54122 ••	Matte Blue Pattern
HP54123 ••	Matte Silver Pattern
HP54MIX ••	HP54116 {3}, HP54117 {3}, HP54118 {3}, and HP54119 {3}

Standard Full Brim


4-Point Ratchet | 11 Variations

HP54110 ••	White
HP54111 ••	Black
HP54112 ••	Gray
HP54113 ••	Slate Gray
HP54120 ••	Red
HP54130 ••	Yellow
HP54131 ••	Hi-Vis Lime
HP54135 ••	Green
HP54141 ••	Hi-Vis Orange
HP54160 ••	Blue
HP54170 ••	Hi-Vis Pink

6-Point Ratchet | 5 Variations

HP56110 •	White
HP56120 •	Red
HP56130 •	Yellow
HP56135 •	Green
HP56160 •	Blue





HPR541 — 4-Point Ratchet
Replacement Suspension



HP6PTSUS — 6-Point
Suspension Strap



Materials

Shell: high impact acrylonitrile-butadiene-styrene (ABS)
Suspension: high density polyethylene (HDPE) & high impact nylon
Sweat band: polyester fabric & polyurethane (PU) foam

General Specifications

Weight: 378 gm
Shell thickness: 1.7 - 4 mm
Dimensions: 31 cm x 27 cm x 15.2 cm
Suspension adjust sizing: 6.5 - 8
Suspensions: 4-point suspension may be converted to 6-point suspension with optional strap
Standards: ANSI/ISEA Z89.1-2014 and Cert. Mod. - CAN/CSA Z94.1-15
Types: Type 1
Classes: Class E, G, and C (Vented: Class C only)
Optional features: hi-vis colors (HV), lower temperature (LT), higher temperature (HT)

Markings

Types: Type 1 offers protection to the top of the head
Classes: Class E (electrical) rated for 20,000 volts | Class G (general) rated for 2,200 volts | Class C (conductive) does not offer electrical protection
HV: meets all requirements for high visibility
LT: provides protection at low temperatures -22°F
HT: provides protection at high temperatures 140°F
Date code: indicates month and year when the shell was molded – does not indicate service life



Product Guidelines

Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use
Never alter or modify the shell or suspension system
Inspect the hard hat each time before use and replace if there is ANY sign of damage
Replace hard hat after it receives a considerable impact
Accessories such as liners have not been tested to the requirement of this standard
Clean only with mild soap and lukewarm water
Store hard hat in a clean, dry place that is out of direct sunlight
Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat
Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage