

### IUS150 - Ultrasoft 9oz Suit-All Top

**Collection:** IFR

**Shell Fabric:** Westex®: 88% FR Cotton, 12% Nylon

**Outer Carton:** 15

#### Product information

**FEATURES** • Engineered for flame resistance and guaranteed for the life of the garment • 50% extended garment wear life over 100% cotton • Soft feel of cotton comfort • Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure • H2S monitor can attach to outside of pocket with strap and elastic fasteners **STANDARDS** • Westex UltraSoft® fabric meets the requirements of: NFPA 2112, CGSB 155.20, NFPA 70E, CSA Z462, ASTM F1506

**IFR**

IFR

#### Standards

NFPA® 2112

NFPA® 70E

ASTM F1506

CGSB 155.20

CSA Z462 Class 1 (Level FR)



#### Features

- Engineered for flame resistance and guaranteed for the life of the garment
- Soft feel of Cotton comfort
- Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure
- H2S monitor can attach to outside of pocket with strap and elastic fasteners



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

IUS150 - Ultrasoft 9oz Suit-All Top

Test House

Carton Dimensions/Weight

| Item        | Colour | Len  | Wid  | Hgt  | Weight(Kg) | Cubic(m³) | EAN13 | GTIN/DUN14   |
|-------------|--------|------|------|------|------------|-----------|-------|--------------|
| IUS150RBR34 |        | 39.0 | 29.0 | 39.0 | 0.6800     | 0.0441    |       | 404340526235 |
| IUS150RBR36 |        | 39.0 | 29.0 | 39.0 | 0.7030     | 0.0441    |       | 404360526239 |
| IUS150RBR38 |        | 39.0 | 29.0 | 39.0 | 0.7030     | 0.0441    |       | 404380526233 |
| IUS150RBR40 |        | 39.0 | 29.0 | 39.0 | 0.7480     | 0.0441    |       | 404400526236 |
| IUS150RBR42 |        | 39.0 | 29.0 | 39.0 | 0.7710     | 0.0441    |       | 404420526230 |
| IUS150RBR44 |        | 39.0 | 29.0 | 39.0 | 0.7710     | 0.0441    |       | 404440526234 |
| IUS150RBR46 |        | 39.0 | 29.0 | 39.0 | 0.8160     | 0.0441    |       | 404460526238 |
| IUS150RBR48 |        | 39.0 | 29.0 | 39.0 | 0.8390     | 0.0441    |       | 404480526232 |
| IUS150RBR50 |        | 39.0 | 29.0 | 39.0 | 0.8620     | 0.0441    |       | 404500526235 |
| IUS150RBR54 |        | 39.0 | 29.0 | 39.0 | 0.8850     | 0.0441    |       | 404540526233 |
| IUS150RBR58 |        | 39.0 | 29.0 | 39.0 | 0.9530     | 0.0441    |       | 404580526231 |