PM30 SERIES

PASSIVE EARMUFF

ANSI S3.19
EN-352-1:2002

NRR 27 dB SNR 30.4 dB

Height Adjustment to Fit Most // Fold-away Padded Headband // Soft foam ear cups // Custom Imprinting Available

- PM3010 Black
- PM3011 Gray
- PM3022 OD Green
- PM3031 Hi-Vis Lime

PM3011

Earmuff Breakdown

Headband: Polyoxymethylene
Headband Adjustment: Polyoxymethylene
Headband Cushion: Polyurethane Foam + Polyvinyl Chloride
Ear Cup and Volume Ring: Polystyrene
Ear Cushion: Polyurethane Foam + Polyvinyl Chloride
Foam Insert: Polyurethane

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

Packaging

Inner Polybag: 1unit
Case: 40 units
Made in Taiwan

NRR ATTENUATION									
FREQUENCY (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
MEANS	20.9	21.9	31.6	40.9	38.7	39.5	38.2	39.0	38.5
STANDARD DEVIATION (dB)	2.4	1.9	3.0	3.1	2.8	2.1	3.0	3.4	2.6

NRR 27dB

SNR ATTENUATION								
FREQUENCY (Hz)	63	125	250	500	1000	2000	4000	8000
MEAN ATTENUATION (dB)	17.8	18.0	22.3	27.2	37.4	33.9	37.4	38.4
STANDARD DEVIATION (dB)	3.5	2.6	2.9	3.1	3.3	2.2	3.5	5.1
APV (dB)	14.3	15.4	19.3	24.1	34.0	31.7	33.9	33.3

SNR: 30.4dB H: 33.0dB M: 37.8dB L: 21.3dB

Updated as of 12.22