

PS38 - Ultra Safety Glasses

Collection: Eye Protection

Range: PPE

Materials: Polycarbonate, Nylon

Inner Pack: 12

Outer Carton: 144

Product information

Stylish wrap around safety glasses with inclinable side arms, molded nose bridge and a PC browguard for extra protection from glare or particles. Ultra spectacles are ideal for longer use thanks to extremely light weight and flexible temples. Safe for working on electrical applications as free from metal.

Eye Protection

PORTWEST® eye protection range includes spectacles, safety goggles and vizors, designed to protect the eyes and face of workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Standards

ANSI/ISEA Z87.1 + (U6)
ANSI/ISEA Z87.1 + (U6 L3)
EN 166 (1 F)
EN 170 (2C-1.2 (clear))
EN 170 (2-1.2 (amber))
EN 172 (5-3.1)



Features

- Lightweight wrap-around design
- Molded browguard protection
- Inclinable side arms for optimum fit
- Flexible arms for ultra comfort
- Non-magnetic - nickel and ferrous free
- Anti-scratch coating for added durability
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines
- New style
- Metal free



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PS38 - Ultra Safety Glasses Commodity Code: 9004901000

Test House

SGS FIMKO Ltd (Notified Body No.: NB: 0598)

Takomotie 8

, Finland

Ethical & Sustainable Commitment: sgs.fimko@sgs.com

Cert No: 0598/PPE/23/3140

SGS United Kingdom Limited (Notified Body No.: AB: 0120)

Rossmore Business Park

CH65 3EN, UK

Cert No: 0120/PPE/230525

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
PS38AMR	Amber	60.0	35.0	36.0	0.0320	0.0756	5036108420766	15036108906656