

Economy Polyurethane Coated Cut Resistant Gloves Made with High-Density Nylon

DESCRIPTION

This lightweight seamless glove grants cut, abrasion, and puncture protection and features a gray-and-white 13-gauge high-density nylon shell. The shell is enhanced by a smooth, gray polyurethane-coated palm.

Each pair is individually packaged in a polybag.

INDUSTRY

Assembly	Glass Handling
Automotive	HVAC
Carpentry	Infrastructure Maintenance
Construction	Machine Operation
Demolition	Maintenance
General Maintenance	Manufacturing



FEATURES

- Component materials comply with FDA regulations for food contact
- 13-gauge high-density nylon fiber shell offers great dexterity
- Polyurethane dip provides superior grip and comfort
- Overcast color on hem for easy size identification
- Knit wrist cuff offers users a secure, comfortable fit and prevents gloves from slipping off during use

SPECIFICATIONS

SHELL	SHELL COLOR	GAUGE	COATING	COATING COLOR	COATING TYPE	FINISH	CUFF	FDA FOOD CONTACT
High-Density Nylon	Gray and White	13-Gauge	Polyurethane	Gray	Palm	Smooth	Knit Wrist	Compliant
CUT	ASTM F2992-15 RESULTS	ABRASION	PUNCTURE	PUNCTURE RESULTS	EN 388 LEVELS			
Level A6	3,400 Grams	Level 4	Level 3	87 Newtons	4X42F			

PACKAGING

	QUANTITY	6(XS)	7(S)	8(M)	9(L)	10(XL)	11(2XL)
PAIR UPC	1	NA	NA	NA	NA	NA	NA
INNER PACK UPC	12/PACK	810033295690	810033295706	810033295713	810033295720	810033295737	810033295744
CASE GTIN	6 PK/CASE	10810033295697	10810033295703	10810033295710	10810033295727	10810033295734	10810033295741
CASE WEIGHT (IN POUNDS)		9.75	9.3	10.35	11.95	12.3	12.25
OVERCAST COLOR		Purple	Red	Green	Brown	Black	Light Blue

ITEM PUG-006

SIZES 6(XS)-11(2XL)

- EN 388 Levels: 4X42F

Meets ANSI/ISEA 105-2016 standard

- Cut Level A6
- ASTM F2992-15 Results = 3,400 grams
- Abrasion Level 4
- Puncture Level 3
- Puncture Results: 87 Newtons

