

PW43 - Comfort Ear Protector

Collection: Ear Muffs
Range: PPE
Materials: ABS, Polystyrene
Outer Carton: 40

Product information

Comfort and robust ear muffLightweight for all day wearPivoting pin cups for better fitPadded headband for comfortHigh attenuation rate

Ear Muffs

Portwest hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colors for earmuffs allow a personalized choice. An updated range of earplugs complete our competitive and performing offer.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Standards

EN 352-1 (SNR 32dB)
ANSI S3.19 (26dB)



Features

- CE-CAT III
- Adjustable length for a secure and comfortable fit
- Padded headband for comfort
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines

	Range
Black	-

PW43 - Comfort Ear Protector

Commodity Code: 6506101000

Test House

Michael & Associates, Inc. (Notified Body No.:)
 2766 W. College Ave Suite 1
 PA 16801, United States
 Cert No: Q1264A

Inspec (Notified Body No.: 0194)
 56 Leslie Hough Way
 M66AJ, UK
 Cert No: PPE 18161204

CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m³)	EAN13	DUN14
PW43BKR	Black	66.0	46.0	56.0	0.2400	0.1700	5036108161430	15036108690548

PERFORMANCES - SOUND ATTENUATION - EN352-1:2002

PW43								
A	Frequency (Hz)	125	250	500	1000	2000	4000	8000
B	Means Attenuation (dB)	19.1	22.4	30.1	38.9	33.4	39.6	37.6
C	Standard Deviation (dB)	2.2	2.5	2.0	2.3	2.2	2.1	2.6
D	Assumed Protection (dB)	16.9	19.9	28.1	36.6	31.2	37.5	35.0
SNR = 32dB H = 34 dB / M = 30 dB / L = 23 dB								

PERFORMANCES - SOUND ATTENUATION - ANSI S3 19-1974 *Tested by Michael & Associates, Inc.*

PW43										
A	Frequency(Hz)	125	250	500	1000	2000	3150	4000	6300	8000
B	Mean Attenuation (dB)	17.8	21.8	29.1	38.4	36.3	40.6	40.6	37.1	39.0
C	Standard Deviation (dB)	2.8	2.3	1.8	2.7	2.7	3.1	3.2	3.8	2.8
NNR (NOISE REDUCTION RATING) = 32dB										

PW43BKR