

ZTEK® READERS

Available In 3 Lens Color | 3 Magnifying Strengths



Black Templates

Part	Lens
S2510R15•••	Clear +1.5
S2510R20•••	Clear +2.0
S2510R25•••	Clear +2.5
S2514R15•	1.5 IR Filter +1.5
S2514R20•	1.5 IR Filter +2.0
S2520R15•	Gray +1.5
S2520R20•	Gray +2.0
S2520R25•	Gray +2.5

- Economical wrap around single lens provides full panoramic view.
- Lens insert strategically placed out of user's direct line of vision.

GENERAL SPECIFICATION

Bridge: 13mm
Lens Base: 10 Curve
Lens Size Diagonal: 64mm
Lens Size Vertical: 44mm
Lens Thickness: 2.5mm
Overall Length (Lens-Tip): 154mm
Overall Width (Hinge-Hinge): 137.5mm
PD: 68mm
Weight: 21gm

PACKAGING

Polybag: 1pc

Inner Box: 6 pcs

Case: 150 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Attractive & stylish unitary lens
Frame	Polycarbonate	Matted finish integral to lens
Side Shield	Polycarbonate	Integral to lens
Nose Piece	Polycarbonate	V bridge - integral to lens
Temple	Polycarbonate	Matte finish - straight back design
Temple Tips	PVC	Soft to prevent slippage
Hinge	Polycarbonate	3 barrel type, integral to frame
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
S2510R15	 Clear +1.5	P Z87 + U6	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
S2510R20	 Clear +2.0	P Z87 + U6	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
S2510R25	 Clear +2.5	P Z87 + U6	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
S2514R15	 1.5 IR Filter +1.5	P Z87 + S	P Z87 +
S2514R20	 1.5 IR Filter +2.0	P Z87 + S	P Z87 +
S2520R15	 Gray +1.5	P Z87 + U6 L2.5	P Z87 +
S2520R20	 Gray +2.0	P Z87 + U6 L2.5	P Z87 +
S2520R25	 Gray +2.5	P Z87 + U6 L2.5	P Z87 +

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

2: Rx

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices