

VENTURE II® READERS

Strategically Placed Lens Inserts



Black Frame

Part	Mag Strength	Lens
SB1810R10•••	+1.0	Clear
SB1810R15•••	+1.5	Clear
SB1810R15T•••	+1.5	Clear Anti-Fog
SB1810R20•••	+2.0	Clear
SB1810R20T•••	+2.0	Clear Anti-Fog
SB1810R25•••	+2.5	Clear
SB1810R25T•••	+2.5	Clear Anti-Fog
SB1810R30•••	+3.0	Clear
SB1820R15•••	+1.5	Gray
SB1820R20•••	+2.0	Gray
SB1820R25•••	+2.5	Gray
SB1820R30•••	+3.0	Gray

Black Frame

Part	Mag Strength	Lens
SB1830R15•••	+1.5	Amber
SB1830R20•••	+2.0	Amber
SB1830R25•••	+2.5	Amber
SB1880R15•••	+1.5	Indoor/Outdoor Mirror
SB1880R20•••	+2.0	Indoor/Outdoor Mirror
SB1880R25•••	+2.5	Indoor/Outdoor Mirror

- Temples adjust to four different lengths.
- 9.75 base curved lens provides full side protection.
- Strategic placement of lens insert is out of user's direct line of vision.
- Nose buds secure the glass and prevent slipping while providing a pillow soft fit.

GENERAL SPECIFICATION

Bridge: 10.5mm
Lens Base: 9.75 Curve
Lens Size Diagonal: 56mm
Lens Size Vertical: 45mm
Lens Thickness: 2.2mm
Overall Length (Lens-Tip): 150-163mm
Overall Width (Hinge-Hinge): 142mm
PD: 68mm
Weight: 27gm
Closest point between lens: 7mm
Closest point between temple tips: 95-98mm

PACKAGING

Polybag: 1pc
Inner Box: 6 pcs
Outer Carton: 150 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Full eye protection
Frame	Polycarbonate	Lens clip in frame
Side Shield	Polycarbonate	Integral to lens
Nose Piece	Bridge - Polycarbonate	Integral to lens
	Nose Pad - PVC	Snap in nose piece
Sleeve	Nylon	4 length position adjust

VENTURE II® READERS

COMPONENT	MATERIAL	FEATURES
Temple	Nylon	Length adjustable
Hinge	Polycarbonate/Nylon	3 barrel type
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB1810R10	 Clear +1.0	P + U6	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
SB1810R15	 Clear +1.5	P + U6	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
SB1810R15T	 Clear +1.5 Anti-fog	P + U6	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
SB1810R20	 Clear +2.0	P + U6	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
SB1810R20T	 Clear +2.0 Anti-fog	P + U6	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
SB1810R25	 Clear +2.5	P + U6	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
SB1810R25T	 Clear +2.5 Anti-fog	P + U6	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
SB1810R30	 Clear +3.0	P + U6	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
SB1820R15	 Gray +1.5	P + U6 L2.5	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
SB1820R20	 Gray +2.0	P + U6 L2.5	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
SB1820R25	 Gray +2.5	P + U6 L2.5	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
SB1820R30	 Gray +3.0	P + U6 L2.5	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
SB1830R15	 Amber +1.5	P + U6	P Z87 + 2
SB1830R20	 Amber +2.0	P + U6	P Z87 + 2
SB1830R25	 Amber +2.5	P + U6	P Z87 + 2
SB1880R15	 Indoor/Outdoor Mirror +1.5	P + U6 L1.7	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
SB1880R20	 Indoor/Outdoor Mirror +2.0	P + U6 L1.7	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07
SB1880R25	 Indoor/Outdoor Mirror +2.5	P + U6 L1.7	P Z87 + 2 / P c SEI CAN/CSA Z94.3-07

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

2: Rx

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices