



Ridgeline® Lens Accessory

STANDARDS

ANSI Z87.1-2020 • // CSA Z94.3-2020 •

One-piece wraparound lens for eye protection // Clips to secure the lens accessory into the safety hard hat // 5-position length adjustment provides the best fit for all head sizes // Optically correct polycarbonate lens with impact resistance against flying particles // Filters out 99.9% of all harmful UV light

-  RIDGE10STM •• Clear **H2MAX** AF
-  RIDGE20STM •• Gray **H2MAX** AF

**Ridgeline Lens Accessories fit both Ridgeline Cap style and Ridgeline Full Brim hard hats. Ridgeline Cap style hard hats are only CSA-approved when worn with the side clips.*



P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM



SPECS

ACCESSORY MATERIALS

Lens	Polycarbonate
Nosepiece	Polycarbonate and TPR
Stretch Arm	Nylon
Clip	Nylon

WEIGHTS AND MEASURES

Lens Thickness	2.3mm
PD	64mm
Lens Base	7 Curve
Weight	33.4gm
Vertical Lens Measurement	54.5mm
Diagonal Lens Measurement	142.5mm
Bridge	24.7mm
Overall Length	171.5mm
Overall Width	167mm

MARKINGS

PART NO.	LENS MARKING	INNER LEFT TEMPLE MARKING	OUTER LEFT TEMPLE MARKING	INNER RIGHT TEMPLE MARKING
RIDGE10STM	PZ87 + U6 X	P Z87 + TAIWAN	PMX	Ridgeline Accessory SEI Z94.3
RIDGE20STM	PZ87 + U6 L2.5 X	P Z87 + TAIWAN	PMX	Ridgeline Accessory SEI Z94.3

LENS MARKING SYMBOLS

P: Manufacturer's Mark
 Z87: ANSI standard for eye and face protection devices
 +: High Impact
 S: Special Purpose
 W: Welding Filter
 X: Tested Anti-fog

UV FILTER TRANSMITTANCE

U6: .01% max effective far UV • .1% max near UV

VISIBLE LIGHT FILTERS

L1.7: 55% Max. Visible Light
 L2.5: 29% Max. Visible Light

TEMPLE MARKING SYMBOLS

P: Manufacturer's Mark
 Z87: ANSI standard for eye and face protection devices
 +: High Impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

