



PERFORMANCE WITH A MULTIPLIER EFFECT.

ZENITH X2 ANSI



STANDARD

ANSI Z89.1 Type I Type II, Class E
All around protection against impact and penetration including front, rear, and sides.

EN 12492

for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact,
4.2.1.4 rear impact
4.2.2 Penetration
4.2.3 Retention system strength
4.2.4 Effectiveness of the retention system



SIZE

Adjustable – from 52 to 63 cm



MATERIAL

EXTERNAL SHELL:
HD Polypropylene



INTERNAL SHELL:

Neopor® Cycled® by BASF | EPS
obtained from chemical recycling
of plastic waste.

HEADBAND:
Soft PA Nylon



TEMPERATURE OF USE

-22°F / +140°F



WEIGHT

1.04 lb



WHE00097

201	204	209
202	205	210
203	208	215

TECHNOLOGIES

- **D-CORE & HD-CROWN TECHNOLOGY** Neopor® Cycled® internal shell that protects from all-around impacts.
- **ADAPTIVE FIT SYSTEM** Size adjustment system that adapts to create a personalized, secure fit.
- **ELECTRIC SHOCK PROTECTION** External shell protects against electrical hazards.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- **DRY+ LINER** Moisture-wicking fabric for enhanced comfort.
- **LATERAL ADJUSTMENT DIVIDER** Side adjustment points on chinstrap for secure fit.
- **ADVANCED ECO-LEATHER CHINSTRAP** 5 adjustment points and EN color-coded fastener.
- **EARMUFF ADAPTER ATTACHMENT POINTS** For adapters to secure earmuffs.
- **RING TO HOOK** Chinstrap loop that securely attaches helmet to a harness.
- **REPLACEABLE LAMP CLIPS** 4 lamp attachment clips designed to be removable.

3

YEARS
GUARANTEE

10

YEARS
LIFE SPAN



SCAN FOR
COMPLETE
COLLECTION