

WV100036

EN



Scratch-resistant and anti-fog polycarbonate eye protection. Visor Screw Set is included. Can be worn with corrective glasses.

Compatible with KASK Superplasma helmet series.

MOUNTING PARTS



TECHNICAL DETAILS



STANDARD
EN ISO 16321
EN 14458



ANSI Z87.1



CATEGORY
II



MATERIAL
Polycarbonate



ENHANCED OPTICAL PERFORMANCE
✓



WEIGHT
80 g



LENGTH
110 mm

**PANORAMIC LENS**

Developed to maximize visibility with minimal viewing distortion.

**COMPATIBLE WITH GLASSES**

Designed for use with corrective glasses.

**ANTI-FOG**

Equipped with an anti-fog treatment to increase wearer visibility in a variety of conditions.

**DRIP PROOF UPPER CONTOUR**

Rubber edge protects eyes from liquid and debris from entering the visor.

**ABRASION AND SCRATCH RESISTANCE**

Lens treatment designed with protection from abrasion and scratches, increased durability and viewing clarity.

**EXTREME TEMP IMPACT RESISTANCE**

Able to withstand impacts at extreme temperatures for use in a variety of environments.

**CUT PROOF EDGE**

Eye shield edge detail designed with a cut proof edge for enhanced wearer safety.

CE MARKINGS

CODE	COLOR	MARKING
WV100036-500	CLEAR	CE EN14458:2018 KASK V2 PLUS MM/YY = BT 2C-1,2 -30°C+50°C KASK UL1,2 DT 1 -5°C+55°C K N CH 7 16321 KASK DT 1-M -5°C+55°C
WV100036-510	SMOKE	CE EN14458:2018 KASK V2 PLUS MM/YY = BT 5-1,4 -30°C+50°C KASK GL1 DT 1 -5°C+55°C K N CH 7 16321 KASK DT 1-M -5°C+55°C
WV100036-520	SILVER MIRROR	CE EN14458:2018 KASK V2 PLUS MM/YY = BT 5-2,5 -30°C+50°C KASK GL2 DT 1 -5°C+55°C K N CH 7 16321 KASK DT 1-M -5°C+55°C

ANSI MARKINGS

CODE	COLOR	MARKING
WV100036-500	CLEAR	ANSI Z87 + U6 X D3
WV100036-510	SMOKE	ANSI Z87 + U6 L1.5 X D3
WV100036-520	SILVER MIRROR	ANSI Z87 + U6 L2.5 X D3

ADDITIONAL INFORMATION

GUARANTEE

3 years starting from the date of purchase.

LIFE SPAN

10 years starting from the date of manufacture. Life span depends on various factors that can cause deterioration such as sudden temperature changes, the amount of exposure to direct sunlight and the intensity of use. Altered vision and scratches are elements that signal the need to check for deterioration of the visor.

CLEANING

Clean only with water and mild soap. Allow to air dry. Do not use chemical detergents, solvents, petrol powders as they are too aggressive and could lower the structural resistance of the visor.

3
YEARS
GUARANTEE

10
YEARS
LIFE SPAN



SCAN FOR
COMPLETE
COLLECTION