



Atoka® ANSI • CSA •



RUBBER
TIPS

Integrated nosepiece // Soft non-slip rubber temple tips provide non-binding fit

Lens and Temples | 8 Variations

	S9110S ••	Clear
	S9110ST ••	Clear AF
	S9120S ••	Gray
	S9120ST ••	Gray AF
	S9130S ••	Amber
	S9160S ••	Infinity Blue
	S9180S ••	I/O Mirror
	S9180ST ••	I/O Mirror AF

General Specifications

Weight: 22.2 gm
Bridge: 12.7 mm
Lens base: 10 curve
Lens size diagonal: 79 mm
Lens size vertical: 44 mm
Lens thickness: 2.5 mm
Overall length (lens - tip): 157 mm
Overall width (hinge - hinge): 137mm

Materials

Lens: polycarbonate
Temple: polycarbonate
Temple Tip: polyvinyl chloride (PVC)
Nosepiece: polycarbonate
Hinge: polycarbonate

Part No.	Lens Marking	Temple Marking
S9110S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9110ST	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9120S	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9120ST	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9130S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9160S	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9180S	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9180ST	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
S: Special Purpose
UV Filter Transmittance
U6: .01% max effective far UV • .1% max near UV
Visible Light Filters
L1.7: 55% Max. Visible Light
L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

ANSI Z87.1+ standards [•] | Canadian CSA Z94.3-15 & third-party certification [•]

For specific lens options visit our website or contact your sales representative.

03/15