



**PYRAMEX**  
Perform At Your Peak

**Cappture™** ANSI CE CSA



DIELECTRIC

Dielectric

Temples extend from browbar to avoid interference with prescription frame's temples

Part No.	Lens and Temples
S9910ST ●●●	AF Clear H2X
S9920ST ●●●	AF Gray H2X



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet Canadian (CSA Z94.3) (●) standards.

## Cappture™

### General Specifications

Weight: 29.5 gm  
 Bridge: 23.1 mm  
 Lens base: 2.5 curve  
 Lens size diagonal: 145.7 mm  
 Lens size vertical: 51.5 mm  
 Lens thickness: 1.8 mm  
 Overall length (lens - tip): 154 mm  
 Overall width (hinge - hinge): 160 mm  
 Closest point between temple tips: 88 mm

### Materials

Lens: polycarbonate  
 Temples: polycarbonate  
 Hinge: polycarbonate  
 Nosepiece: polycarbonate

Part No.	Lens Marking	Temple Marking
S9910ST	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9920ST	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices

#### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

#### Visible Light Filters

L1.7: 55% max visible light  
 L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

