

CAPSHIELD

Capstone® Ratcheting Shield



PART

CAPSHIELD•••

- 4 ventilation holes provide excellent airflow.
- Ratcheting faceshield adjust to 3 positions.
- Capstone goggle with removeable faceshield provides full face protection.
- Includes strap and clips allowing the user to add to either of the Capstone 500 Series goggles.
- Polycarbonate shield conforms to user's face, offering increased protection from impact & dust.

GENERAL SPECIFICATION

Shield Thickness: 2.0mm

Weight: 78gm

Shield size vertical: 177.64mm

Shield size horizontal: 195.58mm

Shield size diagonal: 224.24mm

Strap Length: 232-365mm

Overall width (hinge-hinge): 185mm

CAPSHIELD

Capstone® Ratcheting Shield

PACKAGING

Polybag: 1pc

Outer Carton: 50 pcs

COMPONENT	MATERIAL	FEATURES
Shield	Polycarbonate	Full face protection
Security Button	Polycarbonate	Shield secured on goggle; with angle adjustment

PART	LENS MARKING	FRAME MARKING
CAPSHIELD	P Z87 +	P Z87 + / P c SEI CAN/CSA Z94.3-07

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA standard for protection devices