

Low Temperature Cut/Impact Resistant Gloves

DESCRIPTION

These insulated gloves are constructed with a 10-gauge Tuffalene® UHMWPE shell with a brushed acrylic terry cloth interior for excellent warmth and comfort. The shell is enhanced with TPU impact protection and dipped palm with foam latex rubber which provides excellent grip, abrasion resistance and puncture resistance.

INDUSTRY

Automotive	Farming
Carpentry	Landscaping
Cold Storage	Material Handling
Construction	Warehousing



ITEM **CIA300INT**

SIZES **7(S)-10(XL)**

FEATURES

- One-piece enhanced Tuffalene® UHMWPE seam-free shell with brushed acrylic terry cloth liner for warmth and comfort
- Latex-dipped palm for grip plus abrasion and puncture resistance
- Flexible impact protection on back hand/fingers
- Knit wrist cuff prevents gloves from slipping
- ANSI/ISEA 138 Impact Level (Overall): 1
- ANSI/ISEA 138 Impact Level (Knuckles): 1
- ANSI/ISEA 138 Impact Level (Fingers/Thumb): 2
- ANSI Cut Level A4
- ASTM F2992-15 Results = 1598 grams
- EN 388 Levels: 2X42DP

SPECIFICATIONS

SHELL	SHELL COLOR	GAUGE	LINER	COATING	COATING COLOR	COATING TYPE	CUFF	FINISH	IMPACT PROTECTION
Tuffalene UHMWPE	White and Blue	10-Gauge	Acrylic Terry Cloth	Latex Rubber	Black	Palm	Knit Wrist	Foam	TPU
ANSI/ISEA 138 IMPACT LEVEL (OVERALL)	ANSI/ISEA 138 IMPACT LEVEL (KNUCKLES)	ANSI/ISEA 138 IMPACT LEVEL (FINGERS/THUMB)	ANSI CUT	ASTM F2992-15 RESULTS	EN 388 LEVELS				
1	1	2	Level A4	1,598 Grams	2X42DP				

PACKAGING

	QUANTITY	7(S)	8(M)	9(L)	10(XL)
PAIR UPC	1	NA	NA	NA	NA
INNER PACK GTIN	12/PACK	00816368029061	00816368029078	00816368029085	00816368029092
CASE GTIN	6 PK/CASE	10816368029068	10816368029075	10816368029082	10816368029099
CASE WEIGHT (IN POUNDS)	-	-	-	-	-
OVERCAST COLOR	Red	Green	Brown	Black	

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
Sales@GlobalGlove.com

GlobalGlove.com