

CONAIRE™

ANSI • CSA •



Lightweight //
Rubber temples

Black Frame | 2 Variations

	SB10710D ••	Clear
	SB10720D ••	Gray



MARKINGS

Part No.	Lens Marking	Temple Marking
SB10710D	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB10720D	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

SPECIFICATIONS

Measurements	Materials
Weight: 26.8 gm	Lens: polycarbonate
PD: 64 mm	Side Shield: polycarbonate
Bridge: 10.8 mm	Frame: transparent nylon
Lens base: 6 curve	Temples: polycarbonate
Lens size diagonal: 54.5 mm	Temple tips: thermoplastic rubber
Lens size vertical: 39.5 mm	Screw: stainless steel
Lens thickness: 2.3 mm	
Overall length (lens - tip): 153 mm	
Overall width (hinge - hinge): 129 mm	
Closest point between temple tips: 90.5 mm	
Closest point between lens: 17.5 mm	