



PYRAMEX
Perform At Your Peak™



Emerge® Plus **ANSI** **CSA**



Rubber temple tips

Soft nosepiece provides comfort for extended use

Full Readers

Part No.	Translucent Gray Frame
SG9810R15 ●●	Clear +1.5 Mag
SG9810R20 ●●	Clear +2.0 Mag
SG9810R25 ●●	Clear +2.5 Mag
SG9810R30 ●●	Clear +3.0 Mag

Top Insert Readers

The top insert reader for the Emerge Plus is strategically placed at the top of the lens — perfect for applications in which user is frequently looking up.

Part No.	Translucent Gray Frame
SG9810TR15 ●●	Clear +1.5 Mag
SG9810TR20 ●●	Clear +2.0 Mag
SG9810TR25 ●●	Clear +2.5 Mag

There's more to see at
PyramexSafety.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet Canadian (CSA Z94.3) (●) standards.



PYRAMEX
Perform At Your Peak™

Emerge® Plus

General Specifications

Weight: 31.3 gm
 Bridge: 10.6 mm
 Lens base: 6 curve
 Lens size diagonal: 54.6 mm
 Lens size vertical: 42.5 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 160 mm
 Overall width (hinge - hinge): 129 mm
 Closest point between temple tips: 88 mm

Materials

Lens: polycarbonate
 Frame: nylon
 Temples: polycarbonate
 Temple tips: thermoplastic rubbers (TPR)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Marking	Frame Marking	Temple Marking
SG9810R15	P Z87 + U6	+1.50	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810R20	P Z87 + U6	+2.00	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810R25	P Z87 + U6	+2.50	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810R30	P Z87 + U6	+3.00	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810TR15	P Z87 + U6	+1.50	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810TR20	P Z87 + U6	+2.00	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810TR25	P Z87 + U6	+2.50	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 - 2: Rx
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

Frame Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5
 +3.00: magnification of +3.0

