



Nitrile Dipped Glove

Product Sheet

GL603C5

HPPE | Nitrile | Micro-Foam

ANSI cut A4 | EN388:2003 cut 5

13 gauge cut-resistant HPPE liner // Tear and abrasion resistant // Black color does not show dirt or grime // Foam nitrile absorbs oil to increase grip // Additional foam nitrile coating acts like a sponge, helps increase gripping power

GL603C5 S, M, L, XL, 2XL

Suggested Applications

Assembly Line // Furniture Manufacturer // HVAC // Aerospace // Handling Oily Parts // Construction

Glove Breakdown

Type: Nitrile Dipped Glove
Material: Micro-Foam Nitrile
Liner: 13 Gauge HPPE
Cuff: HPPE & Latex Elastic

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Testing Performance

EN388: 2003 – 4543

Abrasion	1	2	3	4	-	-	-
Circular Blade Cut	1	2	3	4	5	-	-
Tear	1	2	3	4	-	-	-
Puncture	1	2	3	4	-	-	-

ANSI/ISEA 105-2016

Cut	1	2	3	4	5	6	7
-----	---	---	---	---	---	---	---



Glove Sizing

The color of the binding around the cuff indicates the glove size.

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Packaging

Pack: 12 pair
Case: 120 pair
Country of Origin: China

Cleaning

Do not use any chemicals or sharp-edged objects for cleaning the gloves. Cleaning can alter the performance levels of the glove.