



RCSZH33 Series

ANSI Type R Class 3 Not FR CSA Class 2 Level 2 Not FR

Weather resistant hi-vis lime polyester material — Teflon™ treated

Elastic band at the waist and wrists

2" silver reflective material with contrasting color time with X pattern on back

Chest pocket with clear panel and hook and loop closure

2 mic tabs

Drawstring hood

Zipper front closure

PART NO.	COLOR	SIZES
RCSZH3310 ●●	Lime	M, L, XL, 2XL, 3XL, 4XL, 5XL

Pockets

4 OUT

WASHING INSTRUCTIONS

Max 25 washes



Machine wash – cold water – gentle cycle



Do not bleach or use softener



Do not tumble dry



Do not iron



Hang dry

Made in China

There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

RCSZH33 Series Hi-vis work wear meets ANSI/ISEA 107-2015 standards [●] and CAN/CSA Z96-15 standards [●]



STANDARDS

ANSI/ISEA 107-2015 Type R Class 3 Not FR and CAN/CSA Z96-15 Class 2 Level 2 Not FR

GENERAL SPECIFICATIONS

MATERIALS

Outside: 100% polyester and 380gsm fleece with Teflon treatment

Hood lining: 130gsm birdseye material 100% polyester

Contrasting trim: 120gsm solid knit 100% polyester

Reflective tape: China brand flat silver

CLOSURE

Front: 5# black resin zipper from bottom of jacket to top of collar

Waist and wrists: elastic knit

Hood: drawstring

REFLECTIVE STRIPING

One 2" China brand silver reflective stripe applied horizontally dividing black material from lime material

Two 2" China brand silver reflective stripes run vertically from top of horizontal stripes over shoulders to top of back side horizontal stripe

Two 2" China brand silver reflective stripes around both long sleeves

POCKETS

Two lower outside slash pockets

One upper left chest pocket with zipper closure

One upper right clear badge pocket

JACKET MEASUREMENTS (in.)

	M	L	XL	2XL	3XL	4XL	5XL
CHEST MEASUREMENTS	38"-40"	42"-44"	46"-48"	50"-52"	54"-56"	58"-60"	62"-64"
LENGTH	27"	27 1/2"	29"	30 1/2"	32"	34"	35"



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

RCSZH33 Series Hi-vis work wear meets ANSI/ISEA 107-2015 standards (●) and CAN/CSA Z96-15 standards (●)