



Ridgeline® Cap Style **ANSI**

ABS material – strong, yet ultra-light for seemingly weightless protection

Low profile design – offers a low center of gravity for better balance

Rear padded suspension – provides additional level of comfort on the wearers' neck

4-position harness points allows you to move the harness forward, backward, up or down – allowing for the most optimal position for ultimate comfort

Replaceable sweat band – padded fabric and polyurethane foam for all day wear

Vented pressure pad keeps the straps in place providing an additional level of comfort

Easy to grasp knob adjusts the suspension from 6 ½ to 8

Swinging hinge points allows you to find the most comfortable position on the back of your head

Ridgeline cap style hard hats have been tested and pass for reverse orientation

Ridgeline vented cap style hard hats are rated Class C and do not meet Class E or G safety standards for industrial head protection

Custom imprinting available on hard hats



Factory Direct Hydro Dipped

4-Point Ratchet Part No.












- HP44116 •
- HP44116S • **NEW** Ships Nov 2017
- HP44117 •
- HP44117S •
- HP44118 •
- HP44119 •

Color

-  Matte White Graphite Pattern
-  Shiny White Graphite Pattern
-  Matte Black Graphite Pattern
-  Shiny Black Graphite Pattern
-  Matte Copper Pattern
-  Matte Camo Pattern






4-Point Ratchet Part No.

Color

- | | | |
|-----------|---|--|
| HP44110 • |  | White |
| HP44112 • |  | Gray |
| HP44113 • |  | Slate Gray |
| HP44120 • |  | Red |
| HP44130 • |  | Yellow |
| HP44131 • |  | Hi-Vis Lime |
| HP44135 • |  | Green |
| HP44141 • |  | Hi-Vis Orange |
| HP44160 • |  | Blue |
| HP44162 • |  | Light Blue |
| HPR441 |  | 4-point Ratchet Replacement Suspension |









Vented 4-Point Ratchet Part No.

Color

- | | | |
|------------|---|---------------|
| HP44110V • |  | White |
| HP44112V • |  | Gray |
| HP44120V • |  | Red |
| HP44130V • |  | Yellow |
| HP44131V • |  | Hi-Vis Lime |
| HP44141V • |  | Hi-Vis Orange |
| HP44160V • |  | Blue |

6-Point Ratchet Part No.

Color

- | | | |
|-----------|---|--|
| HP46110 • |  | White |
| HP46120 • |  | Red |
| HP46130 • |  | Yellow |
| HP46131 • |  | Hi-Vis Lime |
| HP46135 • |  | Green |
| HP46141 • |  | Hi-Vis Orange |
| HP46160 • |  | Blue |
| HPR461 |  | 6-point Ratchet Replacement Suspension |

There's more to see at
PYRAMEXSAFETY.COM
(P) 800.736.8673 | (F) 901.861.4967

Ridgeline non-vented head protection meets ANSI Z89.1 (•), Type 1, Class E, G, and C. Ridgeline vented head protection meets ANSI Z89.1 (•), Type 1, and Class C. Hi-Vis colors have been tested for the "HV" mark.



PYRAMEX
Perform At Your Peak

Ridgeline® Cap Style

Materials

Shell: high impact acrylonitrile-butadiene-styrene (ABS)

Suspension: high density polyethylene (HDPE) & high impact nylon

Sweat band: polyester fabric & polyurethane (PU) foam

General Specifications

Weight: 358 gm

Shell thickness: 2 - 4 mm

Dimensions: 28 cm x 22 cm x 15.2 cm

Suspension adjust sizing: 6.5 - 8

Suspensions: 4-point & 6-point ratchet

Styles: vented & non-vented

Standards: ANSI/ISEA Z89.1-2014

Types: Type 1


Classes: non-vented Class E, G, and C | vented Class C

Optional features: reverse donning, hi-vis colors (HV), lower temperature (LT), higher temperature (HT)

Markings

Types: Type 1 offers protection to the top of the head

Classes: Class E (electrical) rated for 20,000 volts | Class G (general) rated for 2,200 volts | Class C (conductive) does not offer electrical protection

Reverse donning: accepted models the symbol molded into the brim 

HV: meets all requirements for high visibility

LT: provides protection at low temperatures -22°F

HT: provides protection at high temperatures 140°F

Date code: indicated month and year when the shell was molded – does not indicate service life



Product Guidelines

Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use

Never alter or modify the shell or suspension system

Inspect the hard hat each time before use and replace if there is ANY sign of damage

Replace hard hat after it receives a considerable impact

Accessories such as liners have not been tested to the requirement of this standard

Clean only with mild soap and lukewarm water

Store hard hat in a clean, dry place that is out of direct sunlight

Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat

Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967