



**PYRAMEX**  
Perform At Your Peak



## Ridgeline® Full Brim **ANSI CSA**

Shell constructed from ABS materials

Ratchet suspension is easy to adjust and allows the wearer to modify the fit while wearing hard hat

Replaceable suspensions and headbands available

4-point suspension may be converted to 6-point suspension with optional strap (HP6PTSUS)

Custom imprinting available on hard hats



## Factory Direct Hydro Dipped

4-Point Ratchet Part No.	Color
HP54116 ●●	Matte White Graphite Pattern
HP54116S ●● <b>NEW</b> Ships Nov 2017	Shiny White Graphite Pattern
HP54117 ●●	Matte Black Graphite Pattern
HP54117S ●●	Shiny Black Graphite Pattern
HP54118 ●●	Matte Copper Pattern
HP54119 ●●	Matte Camo Pattern

4-Point Ratchet Part No.	Color
HP54110 ●●	White
HP54111 ●●	Black
HP54113 ●●	Slate Gray
HP54120 ●●	Red
HP54130 ●●	Yellow
HP54131 ●●	Hi-Vis Lime
HP54135 ●●	Green
HP54141 ●●	Hi-Vis Orange
HP54160 ●●	Blue
HP54170 ●●	Hi-Vis Pink
HPR541	Replacement Suspension
HP6PTSUS	6-Point Suspension Strap



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) 800.736.8673 | (F) 901.861.4967

Ridgeline head protection meets ANSI Z89.1 (●), Type 1, Class E, G, and C. Options also meet Canadian CSA Z94.1-2015 (●) standards. Hi-vis colors have been tested for the "HV" mark.



**PYRAMEX**  
Perform At Your Peak

## Ridgeline® Full Brim

### Materials

---

Shell: high impact acrylonitrile-butadiene-styrene (ABS)  
Suspension: high density polyethylene (HDPE) & high impact nylon  
Sweat band: polyester fabric & polyurethane (PU) foam


### General Specifications

---

Weight: 378 gm  
Shell thickness: 1.7 - 4 mm  
Dimensions: 31 cm x 27 cm x 15.2 cm  
Suspension adjust sizing: 6.5 - 8  
Suspensions: 4-point suspension may be converted to 6-point suspension with optional strap  
Standards: ANSI/ISEA Z89.1-2014 and Cert. Mod. - CAN/CSA Z94.1-15  
Types: Type 1  
Classes: Class E, G, and C  
Optional features: hi-vis colors (HV), lower temperature (LT), higher temperature (HT)

### Markings

---

Types: Type 1 offers protection to the top of the head  
Classes: Class E (electrical) rated for 20,000 volts | Class G (general) rated for 2,200 volts | Class C (conductive) does not offer electrical protection  
HV: meets all requirements for high visibility  
LT: provides protection at low temperatures -22°F  
HT: provides protection at high temperatures 140°F  
Date code: indicated month and year when the shell was molded – does not indicate service life 

### Product Guidelines

---

Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use  
Never alter or modify the shell or suspension system  
Inspect the hard hat each time before use and replace if there is ANY sign of damage  
Replace hard hat after it receives a considerable impact  
Accessories such as liners have not been tested to the requirement of this standard  
Clean only with mild soap and lukewarm water  
Store hard hat in a clean, dry place that is out of direct sunlight  
Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat  
Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) 800.736.8673 | (F) 901.861.4967