



Sitecore™ ANSI CE CSA



RUBBER
NOSEPIECE



RATCHETING
TEMPLES



ADJUSTABLE
TEMPLES

Built-in rubber nosepiece

Flexible and ventilated temples

Ratcheting temples

Temples adjust to three different lengths

H2MAX



vimeo.com/pyramex/h2max

Part No.		Black and Gray Frame
SBG10110D ●●		Clear
SBG10110DTM ●●	AF	Clear H2MAX
SBG10120D ●●		Gray
SBG10120DTM ●●	AF	Gray H2MAX
SBG10130D ●●		Amber
SBG10180D ●●		I/O Mirror

Part No.		Gray and Lime Frame
SGL10110D ●●●		Clear
SGL10110DTM ●●●	AF	Clear H2MAX
SGL10120D ●●●		Gray
SGL10120DTM ●●●	AF	Gray H2MAX
SGL10180D ●●●		I/O Mirror



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provides 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European EN166 (●), Canadian CSA Z94.3 (●) – SEI third-party certification.

Sitecore™

General Specifications

Weight: 24.4 gm
Bridge: 10.6 mm
Lens base: 8 curve
Lens size diagonal: 74 mm
Lens size vertical: 41.5 mm
Lens thickness: 2.2 mm
Overall length (lens - tip): 158 mm
Overall width (hinge - hinge): 132.5 mm
Closest point between temple tips: 55 mm

Materials

Lens: polycarbonate
Frame: polycarbonate
Nosepiece: thermoplastic rubber (TPR)
Ratchet: polycarbonate
Sleeve: nylon
Temple: nylon
Screw: stainless steel

Part No.	Lens Marking	Temple Marking
SBG10110D	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10110DTM	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10120D	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10120DTM	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10130D	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10180D	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
SGL10110D	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SGL10110DTM	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SGL10120D	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SGL10120DTM	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SGL10180D	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% max visible light
L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967