



**MCR
SAFETY**

**DC1 R
FR Gear**

Specification Sheet

PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The DC1 coveralls feature a comfortable 88% cotton 12% Nylon twill material that meets the NFPA 2112-2018 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

Available in Regular or Tall Sizes, Red, Gray, Navy, Royal Blue, & Tan

Sizes available: See Spec Sheet



FEATURES:

- **Available in Regular or Tall Sizes, Red, Gray, Navy, Royal Blue, & Tan**
- NFPA 2112 UL Certified
- ASTM F1506 Electric Arc Protection
- NFPA 70E Hazard/Risk Cat HRC2 / ATPV 9.3 cal/cm²
- Max Comfort™ 7 oz. 88% cotton / 12% nylon FR twill fabric
- Sewn with Nomex® Flame Resistant thread
- Three needle reinforced stitching on major seams for durability
- Heavy duty two-way YKK® brass break-away zipper with Nomex® tape
- Protective storm flap with snap closure to cover front zipper
- Two chest pockets with mitered flaps, snap closure, plus pen pocket
- Two front hip pockets on coverall pants
- Side pass through with snap closure
- Two back patch pockets – left pocket with flap and snap closure
- Bi-swing action back gussets for ease of movement and comfort
- Pen pocket on left arm
- Tool pocket on right leg

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2020 MCR Safety - All Rights Reserved



MCR
SAFETY

DC1R
FR Gear

Specification Sheet

- Adjustable snap closure on cuffs of sleeves and legs
- All snaps have reinforcement strips

APPLICATIONS:

Oil and Gas Industry, Electronic Assembly, Fracking, Mining,
Utilities

TECHNICAL DATA FOR: DC1R

Category	FR Gear	NFPA 2112-2018 Certified	Yes
Color	Red	NFPA 70E-2018 Certified	Yes
Material	Flame Resistant, 88% Cotton / 12% Nylon	ASTM 1930 Cert.	Yes
Material Weight	7.0 oz.	ASTM F1506 Cert.	Yes
Components	1 pc Coverall	Hazard Risk Category	CAT2
Flame Resistant	Yes		
Front Closure	YKK 2-Way Zipper & Triple Snap		

Item No:	Chest	Sizing	Back Length	Sweep	Inseam	Color	Case Weight
DC1R34	34	Regular	N/A	N/A	30	Red	25.700
DC1R36	36	Regular	N/A	N/A	30	Red	25.700
DC1R36T	36	Tall	N/A	N/A	32	Red	25.700
DC1R38	38	Regular	N/A	N/A	30	Red	25.700
DC1R38T	38	Tall	N/A	N/A	32	Red	25.700
DC1R40T	40	Tall	N/A	N/A	32	Red	25.700
DC1R40	40	Regular	N/A	N/A	30	Red	25.700
DC1R42T	42	Tall	N/A	N/A	32	Red	25.700
DC1R44T	44	Tall	N/A	N/A	32	Red	25.700
DC1R46T	46	Tall	N/A	N/A	32	Red	25.700
DC1R48T	48	Tall	N/A	N/A	32	Red	25.700
DC1R50T	50	Tall	N/A	N/A	32	Red	25.700
DC1R50	50	Regular	N/A	N/A	30	Red	25.700
DC1R52	52	Regular	N/A	N/A	30	Red	25.700
DC1R52T	52	Tall	N/A	N/A	32	Red	25.700
DC1R54	54	Regular	N/A	N/A	30	Red	25.700
DC1R54T	54	Tall	N/A	N/A	32	Red	25.700
DC1R56	56	Regular	N/A	N/A	30	Red	25.700
DC1R56T	56	Tall	N/A	N/A	32	Red	25.700

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2020 MCR Safety - All Rights Reserved



MCR
SAFETY

DC1R FR Gear

Specification Sheet

Item No:	Chest	Sizing	Back Length	Sweep	Inseam	Color	Case Weight
DC1R58T	58	Tall	N/A	N/A	32	Red	25.700
DC1R58	58	Regular	N/A	N/A	30	Red	26.600
DC1R60T	60	Tall	N/A	N/A	32	Red	25.700
DC1R60	60	Regular	N/A	N/A	30	Red	25.700
DC1R62T	62	Tall	N/A	N/A	32	Red	25.700
DC1R64T	64	Tall	N/A	N/A	32	Red	25.700
DC1R66T	66	Tall	N/A	N/A	32	Red	25.700

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2020 MCR Safety - All Rights Reserved