

PGXI Goggles Series Specification Sheet

PRODUCT DESCRIPTION:

Consumers committed to sourcing premium products take confidence with PGX1®. Four (4) styles feature design elements that include polycarbonate lens and body with thermal plastic rubber (TPR) seal,multiple points of indirect venting,external liquid diversion channel, and internal perspiration channel. Two adjustable strap options are available including elastic or TPR as well as two lens offerings in clear or gray. Additional feature include anti-fog coating.



FEATURES:

- Polycarbonate body and lens with thermo plastic rubber (TPR) seal
- External liquid diversion channels
- Multiple points of indirect venting for increased airflow
- Available with Elastic or TPR adjustable strap

TECHNICAL DATA FOR: PGX110AF

Series Category Dielectric Anti-Fog Case Pack Case Dimensions Case Weight Made In MIL - PRF - 31013		PGX1 Goggles Yes Anti-Fog 60 pair 24.016 x 17.717 x 22.835 33.960 oz. Taiwan N/A		Scratch Resistant Frame Material Packaging ANSI Z87+ AS/NZS 1337.1 CE EN166 ANSI D3 SPLASH ANSI D4 DUST		Yes Polycarbonate White Inner Box Yes Yes N/A N/A	
PGX110AF	Clear	Duramass Anti- Fog	Yes	90	Silver	N/A	N/A
PGX112AF	Gray	Duramass Anti- Fog	Yes	13	Silver	N/A	N/A

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrsafety.com

©2017 MCR Safety - All Rights Reserved



PGXI Goggles Series

Specification Sheet

Item No:	Lens Options:	Lens Coating:	Scratch Resistant:	VLT %:	Frame Color:	Temple Color:	Temple Sleeve:
PGX120AF	Clear	Duramass Anti- Fog	Yes	90	Silver	N/A	N/A
PGX122AF	Gray	Duramass Anti- Fog	Yes	13	Silver	N/A	N/A

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrsafety.com

©2017 MCR Safety - All Rights Reserved