



MCR
SAFETY

PGX1 Goggles Series Specification Sheet

PRODUCT DESCRIPTION:

Consumers committed to sourcing premium products take confidence with PGX1® goggles. Four (4) styles feature design elements that include polycarbonate lens and body with thermal plastic rubber (TPR) seal, multiple points of indirect venting, external liquid diversion channel, and internal perspiration channel. Two adjustable strap options are available including elastic or TPR as well as two lens offerings in clear or gray. Additional feature include anti-fog coating.



FEATURES:

- Polycarbonate body and lens with thermo plastic rubber (TPR) seal
- External liquid diversion channels
- Multiple points of indirect venting for increased airflow
- Available with Elastic or TPR adjustable strap

TECHNICAL DATA FOR: PGX110AF

Series	PGX1	ANSI Z87+	Yes
Category	Goggles	AS/NZS 1337.1	Yes
Goggle Type	Indirect Vented	CE EN166	Yes
Dielectric	Yes	ANSI D3 SPLASH	Yes
Anti-Fog	Yes	ANSI D4 DUST	Yes
Scratch Resistant	Yes	ANSI D5 FINE DUST	Yes
Frame Material	Polycarbonate	Packaging	White Inner Box
Case Pack	60 pair	Case Weight	22.421 lb.
Case Dimensions	19.685 x 18.504 x 18.504	Made In	Taiwan

Item No:	Lens Options:	Lens Coating:	Scratch Resistant:	VLT%:	Frame Color:	Goggle Type:
PGX110AF	Clear	Duramass Anti-Fog	Yes	90	Silver	Indirect Vented
PGX112AF	Gray	Duramass Anti-Fog	Yes	13	Silver	Indirect Vented
PGX120AF	Clear	Duramass Anti-Fog	Yes	90	Silver	Indirect Vented
PGX122AF	Gray	Duramass Anti-Fog	Yes	13	Silver	Indirect Vented



MCR
SAFETY

PGX I
Goggles
Series
Specification Sheet