

TIMBERLAND PRO® Powertrain Sport Alloy Safety Toe SD+



TBOA1B6U001



7-12 13 14 15 MW

USA Men's	7	7.5	8	8.5	9	9.5	10	10.5	11	11.5	12	13	14	15
USA Women's	8.5	9	9.5	10	10.5	11	11.5	12						
United Kingdom	6	6.5	7	7.5	8	8.5	9	9.5	10	10.5	11	12	13	14
Europe	39	40	41	41.5	42	42.5	43	43.5	44	45	46	47	48	49
Centimeters	25.0	26.0	26.0	26.5	27.0	27.5	28.0	28.5	29.0	29.5	30.0	31.0	32.0	33.0

FEATURES:

- Ripstop nylon with abrasion resistant screen-print
- .5mm TPU Toe Overlay for enhanced durability and protection
- Alloy Safety Toe
- Synthetic Heel Overlay for abrasion resistance and support
- Ghillie lacing system
- Non-Mutilating upper
- Cement construction
- Mesh lining with antimicrobial treatment
- Fiberglass shank
- Weight 9M 510g

POLYURETHANE OUTSOLE:

- BASF® rubber like PU balances low density with flexibility, traction and comfort
- Molded inverted cone Anti-Fatigue Technology provides support, cushioning and energy return
- Oil resistant per SATRA TM63
- Heat Resistant up to 248°F using EN/ISO 20344:2004 (120°C)
- Slip resistant
- Abrasion resistant

SINGLE-DENSITY OPEN-CELL POLYURETHANE FOOTBED:

- Self-molding for custom fit
- Durable: resists compression set over time
- Resilient: recovers for the next footstrike
- Moisture-wicking and air-permeable



CSA BLUE PATCH/SD+

- Blue CSA meets CSA standards for Grade 1. When tested in accordance with ASTM F2412, each specimen shall fall within a range of 106 Ohms to 3.5x107 Ohms.



30 Day Comfort Guarantee for US and Canada only