



# Trifecta™

(Steel Punched Lens)

## SPECIAL FEATURES

- Wraparound mesh lens does not fog up or become scratched.
- Provides excellent eye protection for work environments with high humidity and fine particles, such as landscaping, forestry, mining and construction.
- Soft, pliable rubber temple tips secure the spectacle to prevent slipping.
- Stainless steel perforated lens complies with EN 1731:2006.
- Meets ANSI Z87.1+ High Impact (not high mass); CE EN166:2001; Impact rated "F".
- This lens does not provide UV protection.

## GENERAL SPECIFICATIONS

Lens thickness: 0.6mm

Lens Base: 8 curve

Lens size vertical: 44.5 mm

Bridge: 12 mm

Overall Width (hinge-hinge): 140 mm

Closest point between temple tips: 86 mm

PD: 68 mm

Weight: 36 gm

Lens size diagonal: 60.5 mm

Temple length (lens-tip): 162 mm

Closest point between lens: 15 mm

## FRAME & LENS OPTIONS

Frame colors: Various

Lens options: Black mesh lens

| COMPONENT    | MATERIAL                      | FEATURES                                |
|--------------|-------------------------------|-----------------------------------------|
| Lens         | Stainless steel               | 8 base wrap around mesh lens            |
| Frame insert | Nylon                         | Mesh lens insert frame, interchangeable |
| Frame        | Polycarbonate                 | Clipped with mesh frame insert          |
| Nose piece   | Polycarbonate                 | Integral to frame, universal            |
| Temple       | Polycarbonate                 | Straight side type                      |
| Temple tip   | PVC                           | Slipped on temple, spatula type         |
| Hinge        | Polycarbonate / polycarbonate | 3 Barrel Type                           |
| Screw        | Stainless Steel               | Standard Hinge screw                    |

## MARKINGS

Lens: As per standard

Frame: As per standard

## PACKAGING

1 pc in a polybag; 12 pcs in an inner box; 300 pcs in a case

## STANDARDS

Meets ANSI Z87.1